



Thermo Scientific TraceGOLD GC Capillary Columns

Redefining your expectations for GCMS


BIOSZEPARÁCIÓ KFT.
www.bioszeparacio.hu
info@bioszeparacio.hu

Part of Thermo Fisher Scientific

Thermo
SCIENTIFIC

Offering you a leap forward in column performance delivering ultra low bleed, superior inertness and the highest levels of reproducibility guaranteed.


- ▶ **Ultra low bleed** – Leading to greater sensitivity, essential for GCMS applications, while providing extended column lifetime.
- ▶ **High levels of reproducibility** – Both run-to-run and column to column reproducibility. Expect every column to provide the same high levels of performance as the previous one. **Guaranteed.**
- ▶ **Superior inertness** – Offering highly inert columns ensuring excellent peak shape and sensitivity, especially for highly active or difficult compounds.

TraceGOLD
GC columns
demonstrate
ultra low bleed

Low bleed columns are essential for the integrity of analytical results. The amplitude of baseline noise associated with column bleed is indicative of stationary phase stability. A low bleed, stable column produces consistent results, and the low baseline noise enables improved limits of detection with enhanced resolution of low level analytes. Column bleed also contributes to contamination of the MS; minimizing column bleed extends the interval between scheduled maintenance, leading to higher productivity.

This test focuses on the high temperature range close to the operating limits of the columns used, where column bleed is most observable. Columns are held at 325°C for 5 minutes and then the temperature is ramped to 350°C where it is held for another 5 minutes. It can be seen from Figure 1 that the TraceGOLD TG-5MS GC column offers the lowest column bleed of the five columns tested, particularly at the higher temperature of 350°C.

Figure 1: Column bleed obtained from TraceGOLD TG-5MS GC column and 4 leading competitors, clearly demonstrating the low bleed characteristics of this column.



TraceGOLD GC columns ensure excellent run-to-run reproducibility

Run-to-run reproducibility is essential for all analytical laboratories. An advantage of low bleed columns is the greater reproducibility of the stationary phase over a period of time leading to greater run-to-run reproducibility.

The run-to-run reproducibility of the Thermo Scientific TraceGOLD TG-5MS GC column was assessed over 100 runs using a mixture of phenol standards. Figure 2 demonstrates that over a series of 100 injections, the TraceGOLD column provides excellent run-to-run reproducibility.





Figure 2: Overlay of 100 chromatograms showing the column robustness over 100 injections, with excellent retention time stability.



Ask about our new line of Mass Spec Certified Vials - the only vial clean enough for every high sensitivity application



TraceGOLD GC columns ensure excellent batch-to-batch reproducibility

It is essential that there is column-to-column batch reproducibility. Failure to obtain the same high levels of performance for the same type of column can result in methods having to be revalidated and potential doubt being cast on the original data generated. In this test three different columns produced from three different production batches were tested to demonstrate the level of

reproducibility. Each column was initially conditioned at 350°C and then used over five runs to analyze a standard mixture of phenols using an identical set of run conditions for each batch. The data shows that there is excellent batch-to-batch reproducibility for the TraceGOLD TG-5MS GC column.




Figure 3: Analysis of a series of phenols using columns made from different batches. The data demonstrates the excellent batch-to-batch reproducibility obtained with the TraceGOLD TG-5MS GC column.



TraceGOLD GC columns enable analysis of difficult compounds

The acidic nature of the silanol groups prevalent within many GC columns can result in the adsorption of basic compounds, which frequently leads to peak tailing. Poor peak shape affects the sensitivity of an assay, as well as the robustness, as demonstrated in Figure 3.

Treatment of the analytical column by the bonding of basic functional groups onto the column surface reduces the effects of tailing and improves run-to-run reproducibility and sensitivity. Comparison of the chromatograms obtained for the analysis of 4-Picoline and Trimethyl Phosphate, demonstrates the substantially reduced tailing offered by the TraceGOLD TG-5MS AMINE column compared to the competition.





Figure 4: Using the treated TraceGOLD AMINE column substantially reduces the effect of tailing and increases the sensitivity of the assay compared to other columns.

TraceGOLD Column Phase Information

Column	Stationary Phase	Polarity	Maximum Operating Temperature
TG-1MS	100% Dimethyl Polysiloxane	Non-Polar	330°C / 350°C
TG-XLBMS	Proprietary	Non-Polar	360°C
TG-5MS	5% Phenyl Methylpolysiloxane	Non-Polar	330°C / 350°C
TG-SQC	Proprietary	Non-Polar	330°C / 350°C
TG-5MS AMINE	Base Optimized 5% Phenyl Methylpolysiloxane	Non-Polar	300°C / 315°C
TG-5SILMS	Similar to 5% Phenyl Methylpolysiloxane	Non-Polar	330°C / 350°C
TG-5HT	5% Phenyl Methylpolysiloxane	Non-Polar	380°C / 400°C
TG-35MS	35% Phenyl Methylpolysiloxane	Mid-Polarity	300°C / 320°C
TG-35MS AMINE	Base Optimized 35% Phenyl Methylpolysiloxane	Mid-Polarity	220°C
TG-17MS	50% Phenyl Polysiloxane	Mid-Polarity	300°C / 320°C
TG-1301MS	6% Cyanopropylphenyl Methylpolysiloxane	Mid-Polarity	260°C / 280°C
TG-624	6% Cyanopropylphenyl Methylpolysiloxane	Mid-Polarity	240°C
TG-VRX	Proprietary		260°C
TG-VMS	Proprietary		260°C
TG-1701MS	14% Cyanopropylphenyl Methylpolysiloxane	Mid-Polarity	260°C / 280°C
TG-225MS	50% Cyanopropylmethyl Phenylmethylpolysiloxane	Mid-Polarity	240°C
TG-200MS	Trifluoropropyl Methylpolysiloxane	Mid-Polarity	320°C / 340°C
TG-POLAR	90% Cyanopropyl Phenylcyanopropyl Polysiloxane	Polar	275°C
TG-WAXMS	Polyethylene Glycol (PEG)	Polar	260°C
TG-WAXMS A	Acid Optimized Polyethylene Glycol (PEG)	Polar	250°C
TG-WAXMS B	Base Optimized Polyethylene Glycol (PEG)	Polar	220°C
TG-OCP I	Proprietary		340°C
TG-OCP II	Proprietary		340°C
TG-OPP I	Proprietary		330°C
TG-OPP II	Proprietary		330°C
TG-ALC I	Proprietary		260°C
TG-ALC II	Proprietary		260°C
TG-POLAR	90% Cyanopropyl Phenylcyanopropyl Polysiloxane	Polar	275°C
TG-1MT	100% Dimethyl Polysiloxane	Non-Polar	430°C
TG-5MT	5% Diphenyl Polysiloxane	Non-Polar	430°C
TG-Wax MT	Polyethylene Glycol (PEG)	Polar	260°C



CONTACT INFORMATION

North America

USA and Canada
800 332 3331
865 354 4616 fax
chromatography@thermofisher.com

Europe

France
+33 (0) 3 88 67 53 20
+33 (0) 3 88 67 11 68 fax
fr.commande@thermofisher.com

Germany
+49 6103 408 0
+49 6103 408 1111 fax
analyze.de@thermofisher.com

Switzerland
+41 56 618 41 11
+41 56 618 41 41 fax
info.ch@thermofisher.com

United Kingdom
+44 1509 555500
+44 1509 555111 fax
fsuk.sales@thermofisher.com

Asia

Japan
+81 45 453 9220
+81 45 453 9226 fax
info-btd.jp@thermofisher.com

China
800-810-5118
Shanghai: 86-21-64457830 fax
Beijing: 86-1084193583 fax
Guangzhou: 86-20-83486621 fax
info.nnichina@thermofisher.com

India
1800 22 8374 (toll-free)
+91 22 6716 2200
+91 22 6716 2244 fax
contact.LPG.in@thermofisher.com

All Other Enquiries

+44 (0) 1928 534 050
+44 (0) 1928 534 049 fax
salesorders.columns.uk@thermofisher.com

Technical Support

North America
800 332 3331
chromatography.ts@thermofisher.com

Outside North America

+44 (0) 1928 534 440
techsupport.columns@thermofisher.com

For more information, please visit our website at
www.thermoscientific.com/chromatography

© 2011 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

ADDITIONAL INFORMATION

For a comprehensive range of application notes and detailed ordering information, request a copy of our 2010 Thermo Scientific Chromatography Columns and Consumables catalog:

www.thermoscientific.com/catalog

Thermo
SCIENTIFIC