

# New 2009

## FreeMatch DC Inverter



2 power levels: 2,60~3,50 kW.

## Highwall HKEU XR



Automatic opening of the front panel.

Clean air function: ionizer device for air purifying.

Follow me function: a temperature sensor is built in the remote controller and enables a precise management of the temperature setting.

IR remote controller.

Model			HKEU 265 XR	HKEU 355 XR
Type			DC Inverter	DC Inverter
Capacity	Cooling	kW	2,60	3,50
	Heating	kW	2,90	4,09
Power supply		Ph-V-Hz	1-220~230V-50HZ	
		I.U.~O.U.	O.U.	
Wiring cables i.u./o.u. (without ground)		n°	3 (plug cable 6 mt.)	
Refrigerant Pipe Liquid/Gas side		mm(inch.)	6,35(1/4") - 9,52(3/8")	6,35(1/4") - 12,7(1/2")
<b>Specifications</b>				
Indoor Unit	Dimension (WxHxD)	mm	795x270x165	845x286x165
	Net	Kg	10	10,5
Indoor Noise level 1 m (Hi/Mi/Lo)		dB(A)	39/34/29	
Indoor Noise level 2,5 m (Hi/Mi/Lo)		dB(A)	31/26/21	
Moisture Removal		l/h	1,00	1,30
Indoor air flow (Hi/Mi/Lo)		m³/h	570/480/350	700/520/420
Drain hose diameter		mm	20	
Remote Controller (st. equipment)		type	IR Wireless	