


Smart Line DC Inverter



3 power levels: 2,61~5,30 kW.

Highwall HKEU XR



Large LED display showing the room setpoint temperature and operation mode status.

IR remote controller.

Model		HKEU 261 XR	HKEU 351 XR	HKEU 531 XR	
Type		DC Inverter	DC Inverter	DC Inverter	
Capacity	Cooling	kW	2,61	3,50	5,30
	Heating	kW	2,92	3,80	5,60
Power supply		Ph-V-Hz	1-220~230V-50HZ		
		I.U.~O.U.	O.U.		
Wiring cables i.u./o.u. (without ground)		n°	3 (plug cable 6 mt.)		
Refrigerant Pipe Liquid/Gas side		mm(inch.)	6,35(1/4") - 9,52(3/8")	6,35(1/4") - 12,7(1/2")	
Specifications					
Indoor Unit		Dimension (WxHxD)	790x275x190		940x275x198
		Net	Kg		8,5
Indoor Noise level 1 m (Hi/Mi/Lo)		dB(A)	40/35/29	41/37/31	46/43/34
Indoor Noise level 2,5 m (Hi/Mi/Lo)		dB(A)	32/27/21	33/29/23	38/35/26
Moisture Removal		l/h	1,00	1,20	1,80
Indoor air flow (Hi/Mi/Lo)		m ³ /h	500/420/350	550/450/350	755/665/490
Drain hose diameter		mm	ø16		
Remote Controller (st. equipment)		type	IR Wireless		