

aerospace  
climate control  
**electromechanical**  
filtration  
fluid & gas handling  
hydraulics  
pneumatics  
process control  
sealing & shielding



## Brushless Servo Motors

SMH / SMB Motors from 0.35 to 15 Nm  
MH / MB Motors from 0.2 to 285 Nm



ENGINEERING YOUR SUCCESS.

# Contents

<b>SMH / SMB .....</b>	<b>3</b>
<b>Technical Data from 0.35 to 15 Nm .....</b>	<b>3</b>
<b>Curves .....</b>	<b>5</b>
SMB 42 .....	5
SMH 82 .....	5
SMH 60 .....	5
SMH 100 .....	5
SMH 115 .....	6
SMH 142 .....	6
<b>Dimensions and Weights .....</b>	<b>7</b>
<b>Feedback Details .....</b>	<b>8</b>
<b>Options .....</b>	<b>8</b>
<b>Order Code SMH / SMB .....</b>	<b>9</b>
<b>MH / MB .....</b>	<b>10</b>
<b>Technical Data from 0.2 to 285 Nm .....</b>	<b>10</b>
<b>Curves .....</b>	<b>14</b>
MH 56 .....	14
MH 70 .....	14
MH 105 .....	15
MH 145 .....	15
MH 205 .....	16
MB 265 .....	16
<b>Dimensions and Weight .....</b>	<b>17</b>
<b>Feedback Details .....</b>	<b>18</b>
<b>Options .....</b>	<b>19</b>
<b>Order Code MH / MB .....</b>	<b>20</b>

# SMH / SMB

## Servo Motors for Complex and Demanding Applications

The SMH / SMB Series of highly-dynamic brushless servo motors have been designed to combine the cutting-edge technology of Parker Hannifin products with an extremely high performance.

Thanks to the innovative “salient pole” technology, the motor dimensions are drastically reduced with significant advantages in terms of specific torque, overall dimensions and dynamic performances. Compared to traditional-technology brushless servo motor, the specific

torque is about 30 % higher, overall dimensions are considerable reduced and, consequently rotor inertias are extremely low. Thanks to the high quality of Neodymium-Iron-Boron magnets, and also the encapsulation method used to fasten them to the shaft, the SMH / SMB motors can achieve very high accelerations and withstand high overloads without risk of demagnetisation or detachment of the magnets.

Specific applications of the SMH / SMB Series include any type

of automation machinery, especially packaging and handling industry, and all those applications where very high dynamic performances and very low inertias are required.

## Technical Data from 0.35 to 15 Nm



### TECHNICAL SPECIFICATIONS

Power supply	230 VAC or 400 VAC
Protection	IP64/IP65 optional
Ambient temperature	-10/+40 °C

### Options

- Flying cables
- Terminal box (power and resolver)
- External encoder
- Increased inertia
- Brake
- Feedback - resolver, incremental, SinCos, absolute encoder very high dynamic, low inertia
- 2-pole resolver feedback
- 8 poles motor (10 poles SMB 42)
- NdFeB magnets
- Insulation cabling class F, winding class H
- Bearing lubricated for life

### Motors for 230 VAC power supply

Model	Size	Stall		Nominal			Peak Torque	Inertia		Ke	Kt
		Torque	Current	Torque	Speed	Current		No brake	With brake		
		T <sub>065</sub> (T <sub>105</sub> ) [Nm]	I <sub>065</sub> [A]	T <sub>n065</sub> [Nm]	ω [min <sup>-1</sup> ]	I <sub>n065</sub> [A]	T <sub>max</sub> [Nm]	J [kgm <sup>2</sup> ·10 <sup>-3</sup> ]	J [kgm <sup>2</sup> ·10 <sup>-3</sup> ]	Ke [Vs]	Kt [Nm/A <sub>rms</sub> ]
SMB 42 60 0,35...230	42	0.35	0.78	0.15	6000	0.38	0.9	0.013	-----	0.29	0.46
SMH 60 30 0,55...230	60	0.55 (0.68)	0.7	0.48	3000	0.63	1.7	0.018	0.0305	0.44	0.76
SMH 60 45 0,55...230			1.0	0.39	4500	0.74				0.30	0.53
SMH 60 60 0,55...230			1.4	0.24	6000	0.60				0.23	0.40
SMH 60 30 1,4...400			0.95	1.35	1600	0.91				0.85	1.48
SMH 60 60 1,4...400		1.4 (1.7)	1.73	1.20	3000	1.50	4.4	0.03	0.0425	0.47	0.81
SMH 60 45 1,4...230			2.37	1.00	4500	1.69				0.34	0.59
SMH 60 60 1,4...230			2.98	0.80	6000	1.70				0.27	0.47
SMH 60 75 1,4...230			3.85	0.15	7500	0.41				0.21	0.36
SMH 82 10 03...230			1.2	2.9	1000	1.2				1.43	2.48
SMH 82 30 03...400			1.8	2.9	1600	1.8				0.96	1.66
SMH 82 56 03...400	82	3 (3.7)	3.1	2.7	3000	2.8	9	0.14	0.183	0.55	0.96
SMH 82 60 03 ...400			3.5	2.4	3300	2.8				0.49	0.85
SMH 82 45 03 ...230			4.7	2.2	4500	3.4				0.37	0.64
SMH 82 60 03 ...230			6.1	1.5	6000	3.1				0.28	0.49
SMH 82 75 03 ...230			7.5	0.6	7500	1.6				0.23	0.40
SMH 100 30 06...400			100	6 (9)	3.7	5.8				1600	3.6
SMH 100 56 06...400	5.9	5.0			3000	4.9	0.59	1.02			
SMH 100 75 06...400	9.4	3.5			4500	5.5	0.37	0.64			
SMH 100 55 06...230	11.8	2.6			5500	5.1	0.29	0.51			
SMH 100 75 06...230	14.7	0.6			7500	1.5	0.24	0.41			
SMH 115 30 10...400	115	10 (12.5)			6.0	9.0	1600	5.42	32	0.9	1
SMH 115 56 10...400			10.5	8.0	3000	8.40	0.55	0.95			
SMH 115 40 10...230			14.7	7.6	4000	11.19	0.39	0.68			
SMH 115 54 10...230			18.2	7.1	5400	12.93	0.32	0.55			
SMH 142 30 15...400	142	15 (19)	9.7	13.3	1800	8.6	47	1.4	1.6	0.89	1.54
SMH 142 56 15...400			16.0	12.5	3000	13.4				0.54	0.94

### Motors for 400 VAC power supply


Model	Size	Stall		Nominal			Peak torque	Inertia		Ke	Kt
		Torque	Current	Torque	Speed	Current		No brake	With brake		
		T <sub>065</sub> (T <sub>105</sub> ) [Nm]	I <sub>065</sub> [A]	T <sub>n065</sub> [Nm]	ω [min <sup>-1</sup> ]	I <sub>n065</sub> [A]	T <sub>max</sub> [Nm]	J [kgm <sup>2</sup> ·10 <sup>-3</sup> ]	J [kgm <sup>2</sup> ·10 <sup>-3</sup> ]	Ke [Vs]	Kt [Nm/A <sub>rms</sub> ]
SMH 60 30 1,4...400	60	1.4 (1.7)	0.95	1.2	3000	0.81	4.4	0.03	0.0425	0.81	1.48
SMH 60 45 1,4...400			1.37	1.0	4500	0.98				0.59	1.02
SMH 60 60 1,4...400			1.73	0.8	6000	0.99				0.68	0.81
SMH 60 75 1,4...400			2.15	0.15	7500	0.23				0.38	0.65
SMH 82 30 03...400	82	3 (3.7)	1.8	2.7	3000	1.6	9	0.14	0.183	0.96	1.66
SMH 82 45 03 ...400			2.7	2.2	4500	2.0				0.64	1.11
SMH 82 56 03 ...400			3.1	1.6	5600	1.7				0.55	0.96
SMH 82 60 03...400			3.5	1.7	6000	2.0				0.49	0.85
SMH 82 75 03...400			4.4	0.6	7500	0.9				0.39	0.68
SMH 100 30 06...400	100	6 (9)	3.7	5.0	3000	3.1	18	0.336	0.44	0.92	1.60
SMH 100 45 06...400			5.6	3.5	4500	3.3				0.62	1.07
SMH 100 56 06...400			5.9	2.5	5600	2.4				0.59	1.02
SMH 100 75 06...400			9.4	0.6	7500	0.9				0.37	0.64
SMH 115 20 10...400	115	10 (12.5)	4.5	9.0	2000	4.06	32	0.9	1	1.28	2.22
SMH 115 30 10...400			6.0	8.0	3000	4.82				0.96	1.66
SMH 115 40 10...400			8.0	7.6	4000	6.05				0.73	1.26
SMH 115 56 10...400			10.5	6.0	5600	6.30				0.55	0.95
SMH 142 20 15...400	142	15 (19)	6.4	13.0	2000	5.5	47	1.4	1.6	1.36	2.35
SMH 142 30 15...400			9.7	12.5	3000	8.1				0.89	1.54
SMH 142 45 15...400			14.4	10.9	4500	10.5				0.60	1.04
SMH 142 56 15...400			16.0	9.2	5600	9.8				0.54	0.94

These data are referred to a 20 °C ambient temperature

# Curves


## SMB 42

6000 min<sup>-1</sup> 230 V




## SMH 60

1600rpm 230V - 3000rpm 400V




3000rpm 230V - 6000rpm 400V




— S1 65K ΔT — S3 50% 5min — S3 20% 5min  
— S3 10% 5min 230V — S3 10% 5min 400V

## SMH 82

1600rpm 230V - 3000rpm 400V




3000rpm 230V - 5600rpm 400V




— S1 65K ΔT — S3 50% 5min — S3 20% 5min  
— S3 10% 5min 230V — S3 10% 5min 400V

## SMH 100

1600rpm 230V - 3000rpm 400V




3000rpm 230V - 5600rpm 400V



— S1 65K ΔT — S3 50% 5min — S3 20% 5min  
— S3 10% 5min 230V — S3 10% 5min 400V

# SMH 115


1600rpm 230V - 3000rpm 400V



**10**


# SMH 142

1800rpm 230V - 3000rpm 400V




**15**

3000rpm 230V - 5600rpm 400V



**10**

3000rpm 230V - 5600rpm 400V




**15**

— S1 65K ΔT   
 — S3 50% 5min   
 — S3 20% 5min  
— S3 10% 5min 230V   
 — S3 10% 5min 400V


— S1 65K ΔT   
 — S3 50% 5min   
 — S3 20% 5min  
— S3 10% 5min 230V   
 — S3 10% 5min 400V

# Dimensions and Weights

## SMB 42



## SMH 60 - 142



Servo motor	Type	LM/LB/LE/LBE	SF	IM	Flange	DF	F	D x L	b x h x i	t1	V x Z	QF	C x S	G	kg	
<b>SMB 42</b>	0.35	100/--/--/--	6	--	5	3.2	50	9 x 25	----	--	M3 x 9	42	Ø30	j6 x 2.5	57	1
<b>SMH 60</b>	1.4	129.5/161/163/209/142.5/187.5	7	40	8	5.5	63	9 x 20	3 x 3 x 16	10.2	---	60	Ø40	h6 x 2.5	74	1.5
					5	6.0	75	11 x 23	4 x 4 x 18	12.5	M4 x 10	70	Ø60		90	
<b>SMH 82</b>	03	163.5/206.5/183.5/226.5	10	40	8	6.5	100	14 x 30	5 x 5 x 25	16.0	M5 x 12.5	82	Ø80	h6 x 3.5	112	3.6
					5	9.0	115	19 x 40	6 x 6 x 30	21.5	M6 x 16	100	Ø95		135	
<b>SMH 100</b>	06	191.5/238.5/211.5/258.5	10	40	5	9.0	115	19 x 40	6 x 6 x 30	21.5	M6 x 16	100	Ø95	h6 x 3.5	135	4.7
					24 x 50	8 x 7 x 40	27.0	M8 x 19								
<b>SMH 115</b>	10	220/265/220/265	10	41.5	8	9.0	130	19 x 40	6 x 6 x 30	21.5	M6 x 16	115	Ø95	h6 x 3.5	156	7.7
					7	9.0	130	24 x 50	8 x 7 x 40	27.0	M8 x 19	130	Ø110		156	
					5	11	165	28 x 60	8 x 7 x 50	31.0	M10 x 22	145	Ø130		196.5	
<b>SMH 142</b>	15	243/293/243/293	12	41.5	5	11	165	19 x 40	6 x 6 x 30	21.5	M6 x 16	142	Ø130	h6 x 3.5	192.5	13
								24 x 50	8 x 7 x 40	27.0	M8 x 19					
								28 x 60	8 x 7 x 50	31.0	M10 x 22					

mm for dimensions, kg for weight

# Feedback Details

Code	Description
<b>Incremental encoder</b>	
A1	Incremental encoder 2000 i/t, 8 poles Precision $\pm 32''$ , Differential Line Driver 20 mA
A2	Incremental encoder 2048 i/t, 8 poles Precision $\pm 32''$ , Differential Line Driver 20 mA
A3	Incremental encoder 4096 i/t, 8 poles Precision $\pm 16''$ , Differential Line Driver 20 mA
B1	Incremental encoder 3000 i/t, 4 poles Precision $\pm 22''$ , Differential Line Driver 20 mA
B3	Incremental encoder 2048 i/t, 8 poles Precision $\pm 32''$ , Differential Line Driver 20 mA
B8	Incremental encoder 3000 i/t, 8 poles Precision $\pm 22''$ , Differential Line Driver 20 mA
C2	Incremental encoder 2048 i/t, 4 poles Precision $\pm 32''$ , Differential Line Driver 20 mA
<b>Absolute encoder Hiperface</b>	
C6	Single turn optical encoder, 1 Vpp, 128 sinusoid/t, Hiperface Protocol, 4096 positions/g Precision $\pm 320''$
C7	Single turn optical encoder, 1 Vpp, 128 sinusoid/t, Hiperface Protocol, 4096 positions/g, 4096 turns Precision $\pm 320''$
A6	Single turn optical encoder, 1 Vpp, 1024 sinusoid/t, Hiperface Protocol, 32 768 positions/g Precision $\pm 90''$
A7	Single turn optical encoder, 1 Vpp, 1024 sinusoid/t, Hiperface Protocol, 32 768 positions/g, 4096 turns Precision $\pm 90''$
<b>Absolute encoder EnDat</b>	
D5	Multiturn optical encoder, 1 Vpp, 512 sinusoid/t, EnDat Protocol, 8192 positions/t , 4096 turn Precision $\pm 60''$
B6	Single turn optical encoder, 1 Vpp, 2048 sinusoid/t, EnDat Protocol, 8192 positions/t Precision $\pm 20''$
C8	Multiturn optical encoder, 1 Vpp, 2048 sinusoid/t, EnDat Protocol, 8192 positions/t , 4096 turns Precision $\pm 20''$
C9	Single turn optical encoder, 1 Vpp, 32 sinusoid/t, EnDat Protocol, 131 072 positions/t Precision $\pm 400''$
B9	Multiturn optical encoder, 1 Vpp, 32 sinusoid/t, EnDat Protocol, 131 072 positions/t , 4096 turns Precision $\pm 400''$
F2	Multiturn optical encoder, 1 Vpp, 512 sinusoid/t, EnDat Protocol, 8192 positions/t, 4096 turn Precision $\pm 60''$
F3	Single turn optical encoder, 1 Vpp, 512 sinusoid/t, EnDat Protocol, 8192 positions/t, 4096 turn Precision $\pm 60''$

# Options

Code	Option description	Motor sizes						
		SMB 42	SMH 60	SMH 82	SMH 100	SMH 115	SMH 142	
A	Holding brake 24 VDC		√	√	√	√	√	
4	Flange B14			√	√			
5	Flange B5	√	√	√	√	√	√	
7	Flange B7			√		√		
8	Flange B8		√	√	√	√		
9	Flange B9					√		
S	Smooth shaft	√	√	√	√	√	√	
0V	Cables output and flying connectors Faston	√	√					
2IB/2ID	Axial Interconnectron connectors cables output front/back		√	√	√	√	√	
2I	Axial Interconnectron connectors rotary cables output					√	√	
IP64	Protections	√	√	√	√	√	√	
IP65 (optional)		√	√	√	√	√	√	
B3/B1/B8/C2	Feedback		√	√				
C6/C7			√	√				
C9/D5/C8/B9/B6			√	√	√	√	√	
A6/A7			√	√	√	√	√	
F3/F2			√					
A1/A2/A3				√	√	√	√	√
M		Increased inertia (middle inertia)		√	√	√	√	√
230 V	Supply voltage	√	√	√	√	√	√	
400 V			√	√	√	√	√	

## Order Code SMH / SMB

SM...	A	60	30	1,4	5	11	S	2IB	64	F2	M	4
1	2	3	4	5	6	7	8	9	10	11	12	13

1	Motors family	SMH / SMB: Motor with resolver (integrated) SME: Encoder feedback (integrated)										
2	Brake	A: Holding brake										
3	Motor size	42/60/82/100/115/142										
4	Nominal speed	[100 min <sup>-1</sup> ] - example 30 = 3000 min <sup>-1</sup>										
5	Stall torque	65K (T <sub>065</sub> ) [Nm] - example 1.4 = 1.4 Nm										
6	Flange	4: Flange B14										
		5: Flange B5										
		7: Flange B7										
		8: Flange B8										
		9: Flange B9										
7	Shaft diameter	6/9/11/14/19/24/28 [mm]										
8	Smooth shaft (without key)	S										
9	Cables and connectors	0V: Cables output and flying connectors Faston										
		2IB/2ID: Axial Interconnectron connectors cables output front/back										
		2I: Axial Interconnectron connectors rotary cables output										
10	Protections	64: IP64										
		65: IP65										
11	Feedback	please see page with options										
12	Inertia	M: Middle inertia										
13	Power supply	2: 230 VAC										
		4: 400 VAC										

### STANDARDS

In compliance with: EN 60034-5, EN 60529, EN 60529/A1. Marked  Marked  (except SMB 42)

# MH / MB

## High-Performance Brushless Servo Motors

The MH / MB series caters for torques in the range of 0.2 to 285 Nm, speeds up to 10000 min<sup>-1</sup> and includes a total of 75 models available across 6 frame sizes. Thanks to the high quality and performance of the Neodymium-Iron-Boron magnets, and also the encapsulation method used to fasten them to the shaft, the MH / MB series of motors can achieve very high accelerations and withstand high overload without the risk of demagnetisation or detachment of the magnets.

Furthermore, shaft and flange size flexibility on all models provides the user with the possibility to optimise their motor selection for any given application.

Adequate mechanical over-sizing, low inertia in an extra-strong mechanism and a broad range of models permits the application of the MH / MB series in all fields where high dynamic performance and utmost reliability are crucial features.

Typical applications include any type of automatic machinery, especially in

the product packaging and handling industry, and wherever the demand exists for axis speed and position synchronisation.

## Technical Data from 0.2 to 285 Nm



TECHNICAL SPECIFICATIONS	
Power supply	230 VAC or 400 VAC
Protection	IP64/IP65 optional
Ambient temperature	-10/+40 °C

### Available Options

- Flying cables
- Terminal box (power and resolver)
- External encoder
- Increased inertia
- Brake
- Feedback - resolver/incremental/ SinCos/absolute encoder full range of motors
- 2-pole resolver feedback
- 4 and 8 poles motor
- NdFeB magnets
- Insulation cabling class F, winding class H
- Bearing lubricated for life

## Motors for 230 VAC power supply

Model	Size	Stall		Nominal			Peak	Inertia		Ke	Kt	
		Torque	Current	Torque	Speed	Current	Torque	No brake	With brake	Ke	Kt	
		T <sub>065</sub> (T <sub>105</sub> ) [Nm]	I <sub>065</sub> [A]	T <sub>n065</sub> [Nm]	ω [min <sup>-1</sup> ]	I <sub>n065</sub> [A]	T <sub>max</sub> [Nm]	J [kgm <sup>2</sup> ·10 <sup>-3</sup> ]	J [kgm <sup>2</sup> ·10 <sup>-3</sup> ]	Ke [Vs]	Kt [Nm/A <sub>rms</sub> ]	
MH 56 50 0,2...400	56	0.2 (0.40)	0.27	0.21	2500	0.26	1.3	0.011	0.028	0.48	0.83	
MH 56 95 0,2...400			0.46	0.19	5000	0.42				0.28	0.48	
MH 56 100 0,2...230			0.84	0.15	10000	0.60				0.15	0.26	
MH 56 50 0,4...400		0.4 (0.80)	0.49	0.40	2500	0.46	2.5	0.016	0.033	0.52	0.91	
MH 56 95 0,4...400			0.84	0.35	5000	0.71				0.30	0.53	
MH 56 100 0,4...230			1.52	0.21	10000	0.81				0.17	0.29	
MH 56 50 0,6...400		0.6 (1.14)	0.67	0.60	2500	0.63	3.6	0.021	0.038	0.57	0.99	
MH 56 95 0,6...400			1.21	0.51	5000	0.98				0.32	0.55	
MH 56 100 0,6...230			2.18	0.18	10000	0.71				0.18	0.31	
MH 70 37 0,5...400	70	0.5 (0.9)	0.44	0.5	2000	0.43	2.8	0.026	0.055	0.67	1.17	
MH 70 70 0,5...400			0.72	0.4	3800	0.66				0.41	0.71	
MH 70 75 0,5...230			1.37	0.4	7500	1.00				0.22	0.38	
MH 70 37 0,1...400		1.0 (1.6)	0.84	1.0	2000	0.80	5.1	0.040	0.069	0.72	1.25	
MH 70 70 0,1...400			1.39	0.8	3800	1.23				0.42	0.72	
MH 70 75 0,1...230			2.65	0.5	7500	1.43				0.23	0.39	
MH 70 37 1,5...400		1.5 (2.2)	1.23	1.5	2000	1.18	6.8	0.054	0.083	0.73	1.27	
MH 70 70 1,5...400			2.25	1.4	3800	1.96				0.42	0.72	
MH 70 75 1,5...230			4.07	0.7	7500	1.85				0.23	0.39	
MH 70 37 0,2...400		2.0 (2.7)	1.55	1.9	2000	1.47	8.4	0.068	0.097	0.78	1.36	
MH 70 70 0,2...400			2.82	1.7	3800	2.40				0.43	0.75	
MH 70 75 0,2...230			5.36	0.6	7500	1.74				0.23	0.39	
MH 70 37 2,5...400		2.5 (3.1)	1.90	2.4	2000	1.82	9.8	0.081	0.11	0.79	1.36	
MH 70 70 2,5...400			3.56	2.1	3800	3.01				0.42	0.73	
MH 70 75 2,5...230			6.77	0.6	7500	1.77				0.22	0.38	
MH 105 30 0,2...400		105	2.2 (3.5)	1.5	2.2	1600	1.4	11.0	0.19	0.253	0.9	1.63
MH 105 45 0,2...400				2.1	2.1	2500	2.0				0.6	1.11
MH 105 60 0,2...400				2.8	2.1	3000	2.6				0.5	0.83
MH 105 50 0,2...230			4.3	1.8	5000	3.5	0.3	0.55				
MH 105 30 0,4...400			4.0 (6.1)	2.6	4.0	1600	2.5	19.5	0.34	0.403	1.0	1.65
MH 105 45 0,4...400				3.8	3.7	2500	3.5				0.7	1.13
MH 105 60 0,4...400	5.0			3.6	3000	4.4	0.5				0.85	
MH 105 50 0,4...230	7.4		2.7	5000	5.0	0.3	0.58					
MH 105 30 0,6...400	6.0 (8.3)		3.9	5.9	1600	3.7	26.2	0.48	0.543	1.0	1.65	
MH 105 45 0,6...400			5.6	5.5	2500	5.0				0.7	1.15	
MH 105 60 0,6...400			7.4	5.2	3000	6.4				0.5	0.87	
MH 105 50 0,6...230	11.2		3.6	5000	6.7	0.3	0.58					
MH 105 30 0,8...400	8.0 (10.0)		5.2	7.8	1600	5.0	31.7	0.62	0.683	1.0	1.65	
MH 105 45 0,8...400			7.5	7.2	2500	6.6				0.7	1.15	
MH 105 60 0,8...400			9.7	6.8	3000	8.2				0.5	0.88	
MH 105 50 0,8...230			14.2	4.4	5000	7.9				0.4	0.61	
MH 145 10 0,4...400	145		4.5 (9)	1.1	4.6	550	1.1	28	0.78	0.975	2.1	3.65
MH 145 20 0,4...400				2.3	4.6	1100	2.4				1.2	2.03
MH 145 30 0,4...400				3.4	4.5	1600	3.3				0.8	1.42
MH 145 45 0,4...400				4.7	4.3	2500	4.5				0.6	1.01
MH 145 40 0,4...230				8.1	4.1	4000	7.2				0.4	0.60
MH 145 10 0,8...400		8.7 (16)	2.0	8.7	550	2.0	49	1.05	1.245	2.7	4.69	
MH 145 20 0,8...400			3.7	8.7	1100	3.6				1.4	2.49	
MH 145 30 0,8...400			5.4	8.6	1600	5.2				1.0	1.70	
MH 145 45 0,8...400			8.2	8.1	2500	7.4				0.7	1.14	
MH 145 40 0,8...230			12.3	7.0	4000	9.7				0.4	0.76	

### Motors for 230 VAC power supply

Model	Size	Stall		Nominal			Peak Torque	Inertia		Ke	Kt
		Torque	Current	Torque	Speed	Current	T <sub>max</sub> [Nm]	No brake	With brake	Ke [Vs]	Kt [Nm/A <sub>rms</sub> ]
		T <sub>065</sub> (T <sub>105</sub> ) [Nm]	I <sub>065</sub> [A]	T <sub>n065</sub> [Nm]	ω [min <sup>-1</sup> ]	I <sub>n065</sub> [A]		J [kgm <sup>2</sup> ·10 <sup>-3</sup> ]	J [kgm <sup>2</sup> ·10 <sup>-3</sup> ]		
MH 145 10 15...400	145	15.0 (27)	3.3	15.0	550	3.2	86	1.60	1.795	2.9	4.94
MH 145 20 15...400			6.2	14.7	1100	5.9				1.5	2.59
MH 145 30 15...400			9.1	14.3	1600	8.5				1.0	1.78
MH 145 45 15...400			14.2	13.6	2500	12.5				0.7	1.14
MH 145 40 15...230			21.3	10.9	4000	15.0				0.4	0.76
MH 145 10 22...400		22.0 (37)	4.7	21.9	550	4.6	117	2.15	2.345	2.9	5.03
MH 145 20 22...400			8.9	21.3	1100	8.4				1.5	2.65
MH 145 30 22...400			13.1	20.8	1600	12.1				1.0	1.80
MH 145 45 22...400			20.8	19.1	2500	17.6				0.7	1.13
MH 145 40 22...230			31.1	13.4	4000	18.6				0.4	0.76
MH 145 10 28...400		28.0 (45)	5.9	27.8	550	5.8	143	2.70	2.895	2.9	5.07
MH 145 20 28...400			11.3	26.9	1100	10.6				1.5	2.65
MH 145 30 28...400			17.0	26.2	1600	15.5				1.0	1.78
MH 145 45 28...400			26.5	23.2	2500	21.4				0.7	1.13
MH 145 40 28...230			39.6	14.1	4000	19.7				0.4	0.76
MH 205 20 15...400	205	15 (22)	6.3	14.7	1150	6.2	69	3.5	4.035	1.4	2.38
MH 205 30 15...400			8.6	14.4	1700	8.3				1	1.74
MH 205 10 28...400		28 (39)	6.9	28.6	550	6.9	123	5	5.535	2.5	4.35
MH 205 20 28...400			13.0	28.2	1150	12.7				1.3	2.31
MH 205 30 28...400		20.1	27.6	1700	19.3	0.9	1.50				
MH 205 10 50...400		50 (70)	12.4	51.3	550	12.3	222	8	8.535	2.5	4.35
MH 205 20 50...400			22.1	50.0	1150	21.3				1.4	2.45
MH 205 30 50...400		33.1	48.0	1700	30.8	0.9	1.63				
MH 205 10 70...400		70 (98)	16.8	71.1	550	16.5	310	11	11.535	2.6	4.49
MH 205 20 70...400			30.7	68.6	1150	29.3				1.4	2.45
MH 205 30 70...400			46.1	65.0	1700	41.7				0.9	1.63
MH 205 10 90...400		90 (126)	22.1	90.9	550	21.8	398	14	14.535	2.5	4.35
MH 205 20 90...400			44.3	87.0	1150	41.8				1.3	2.18
MH 205 30 90...400			59	81.7	1700	52.4				0.9	1.63

### Motors for 400 VAC power supply

Model	Size	Stall		Nominal			Peak Torque	Inertia		Ke	Kt
		Torque	Current	Torque	Speed	Current	T <sub>max</sub> [Nm]	No brake	With brake	Ke [Vs]	Kt [Nm/A <sub>rms</sub> ]
		T <sub>065</sub> (T <sub>105</sub> ) [Nm]	I <sub>065</sub> [A]	T <sub>n065</sub> [Nm]	ω [min <sup>-1</sup> ]	I <sub>n065</sub> [A]		J [kgm <sup>2</sup> ·10 <sup>-3</sup> ]	J [kgm <sup>2</sup> ·10 <sup>-3</sup> ]		
MH 56 50 0,2...400	56	0.2 (0.40)	0.27	0.19	5000	0.24	1.3	0.011	0.028	0.48	0.83
MH 56 95 0,2...400			0.46	0.16	9500	0.36				0.28	0.48
MH 56 50 0,4...400		0.4 (0.80)	0.49	0.34	5000	0.40	2.5	0.016	0.033	0.52	0.91
MH 56 95 0,4...400			0.84	0.23	9500	0.48				0.30	0.53
MH 56 50 0,6...400		0.6 (1.14)	0.67	0.50	5000	0.54	3.6	0.021	0.038	0.57	0.99
MH 56 95 0,6...400			1.21	0.25	9500	0.51				0.32	0.55
MH 70 37 0,5...400	70	0.5 (0.9)	0.44	0.5	3700	0.41	2.8	0.026	0.055	0.67	1.17
MH 70 70 0,5...400			0.72	0.4	7000	0.55				0.41	0.71
MH 70 37 01...400		1.0 (1.6)	0.84	0.9	3700	0.74	5.1	0.040	0.069	0.72	1.25
MH 70 70 01...400			1.39	0.6	7000	0.85				0.42	0.72
MH 70 37 1,5...400		1.5 (2.2)	1.23	1.3	3700	1.07	6.8	0.054	0.083	0.73	1.27
MH 70 70 1,5...400			2.25	0.8	7000	1.27				0.42	0.72
MH 70 37 2,0...400		2.0 (2.7)	1.55	1.7	3700	1.32	8.4	0.068	0.097	0.78	1.36
MH 70 70 2,0...400			2.82	0.9	7000	1.35				0.43	0.75
MH 70 37 2,5...400		2.5 (3.1)	1.90	2.1	3700	1.60	9.8	0.081	0.11	0.79	1.36
MH 70 70 2,5...400			3.56	1.2	7000	1.73				0.42	0.73




### Motors for 400 VAC power supply

Model	Size	Stall		Nominal			Peak Torque	Inertia		Ke	Kt
		Torque	Current	Torque	Speed	Current		No brake	With brake		
		T <sub>065</sub> (T <sub>105</sub> ) (Nm)	I <sub>065</sub> (A)	T <sub>n065</sub> (Nm)	ω (min <sup>-1</sup> )	I <sub>n065</sub> (A)	T <sub>max</sub> (Nm)	J (kgm <sup>2</sup> ·10 <sup>-3</sup> )	J (kgm <sup>2</sup> ·10 <sup>-3</sup> )	Ke (Vs)	Kt (Nm/A <sub>rms</sub> )
MH 105 30 02...400	105	2.2 (3.5)	1.5	2.1	3000	1.4	11.0	0.19	0.253	0.9	1.63
MH 105 45 02...400			2.1	1.9	4500	1.8				0.6	1.11
MH 105 60 02...400			2.8	1.7	6000	2.2				0.5	0.83
MH 105 30 04...400		4.0 (6.1)	2.6	3.6	3000	2.3	19.5	0.34	0.403	1.0	1.65
MH 105 45 04...400			3.8	3.0	4500	2.8				0.7	1.13
MH 105 60 04...400			5.0	2.4	6000	3.0				0.5	0.85
MH 105 30 06...400		6.0 (8.3)	3.9	5.3	3000	3.4	26.2	0.48	0.543	1.0	1.65
MH 105 45 06...400			5.6	4.1	4500	3.8				0.7	1.15
MH 105 60 06...400			7.4	3.0	6000	3.7				0.5	0.87
MH 105 30 08...400		8.0 (10.0)	5.2	6.9	3000	4.4	31.7	0.62	0.683	1.0	1.65
MH 105 45 08...400			7.5	5.2	4500	4.9				0.7	1.15
MH 105 60 08...400			9.7	3.6	6000	4.4				0.5	0.88
MH 145 10 04...400	145	4.5 (9)	1.1	4.5	1000	1.1	28	0.78	0.975	2.1	3.65
MH 145 20 04...400			2.3	4.5	2000	2.3				1.2	2.03
MH 145 30 04...400			3.4	4.3	3000	3.2				0.8	1.42
MH 145 45 04...400		4.7	3.9	4500	4.0	0.6	1.01				
MH 145 10 08...400		8.7 (16)	2.0	8.7	1000	1.9	49	1.05	1.245	2.7	4.69
MH 145 20 08...400			3.7	8.4	2000	3.5				1.4	2.49
MH 145 30 08...400			5.4	7.9	3000	4.8				1.0	1.70
MH 145 45 08...400		8.2	7.1	4500	6.6	0.7	1.14				
MH 145 10 15...400		15.0 (27)	3.3	14.8	1000	3.1	86	1.60	1.795	2.9	4.94
MH 145 20 15...400			6.2	13.7	2000	5.5				1.5	2.59
MH 145 30 15...400			9.1	12.7	3000	7.5				1.0	1.78
MH 145 45 15...400		14.2	9.8	4500	9.1	0.7	1.14				
MH 145 10 22...400	22.0 (37)	4.7	21.4	1000	4.5	117	2.15	2.345	2.9	5.03	
MH 145 20 22...400		8.9	19.4	2000	7.6				1.5	2.65	
MH 145 30 22...400		13.1	17.3	3000	10.1				1.0	1.80	
MH 145 45 22...400	20.8	11.6	4500	10.8	0.7	1.13					
MH 145 10 28...400	28.0 (45)	5.9	27.1	1000	5.6	143	2.70	2.895	2.9	5.07	
MH 145 20 28...400		11.3	23.9	2000	9.4				1.5	2.65	
MH 145 30 28...400		17.0	21.1	3000	12.5				1.0	1.78	
MH 145 45 28...400	26.5	10.0	4500	9.4	0.7	1.13					
MH 205 20 15...400	205	15 (22)	6.3	14.1	2000	5.9	69	3.5	4.035	1.4	2.38
MH 205 30 15...400			8.6	13.4	3000	7.7				1	1.74
MH 205 10 28...400		28 (39)	6.9	28.2	1000	6.8	123	5	5.535	2.5	4.35
MH 205 20 28...400			13.0	27.3	2000	12.3				1.3	2.31
MH 205 30 28...400		20.1	25.7	3000	18.0	0.9	1.50				
MH 205 10 50...400		50 (70)	12.4	50.4	1000	12.1	222	8	8.535	2.5	4.35
MH 205 20 50...400			22.1	47.0	2000	20.1				1.4	2.45
MH 205 30 50...400		33.1	41.7	3000	26.8	0.9	1.63				
MH 205 10 70...400		70 (98)	16.8	69.4	1000	16.1	310	11	11.535	2.6	4.49
MH 205 20 70...400			30.7	62.9	2000	26.9				1.4	2.45
MH 205 30 70...400		46.1	52.3	3000	33.7	0.9	1.63				
MH 205 10 90...400		90 (126)	22.1	88.2	1000	21.2	398	14	14.535	2.5	4.35
MH 205 20 90...400	44.3		78.3	2000	37.7	1.3				2.18	
MH 205 30 90...400	59.0	61.6	3000	39.7	0.9	1.63					
MB 265 10 75...400	265	75 (95)	14.6	75	1000	14.1	240	22		3.1	5.3
MB 265 20 75...400			28.5	67	2000	25.1				1.5	2.7
MB 265 30 75...400			43.3	57	3000	32.2				1.0	1.8
MB 265 10 150...400		150 (190)	28.5	144	1000	26.9	480	36		3.1	5.3
MB 265 20 150...400			64.6	127	2000	53.7				1.4	2.4
MB 265 30 150...400		86.0	94	3000	53.0	1.0	1.8				
MB 265 10 220...400		220 (280)	41.5	208	1000	39.0	695	49		3.1	5.3
MB 265 20 220...400			82.8	176	2000	65.8				1.5	2.7
MB 265 30 220...400		123.6	114	3000	63.9	1.0	1.8				
MB 265 10 285...400		285 (360)	48.2	266	1000	44.9	900	63		3.4	5.9
MB 265 20 285...400			120.7	220	2000	92.9				1.4	2.4

# Curves

## MH 56






5000rpm 230V 9500rpm 400V



— S1 65K ΔT   
 — S3 50% 5min   
 — S3 20% 5min  
— S3 10% 5min 230V   
 — S3 10% 5min 400V

## MH 70





3800 rpm 230V 7000 rpm 400V



— S1 65K ΔT   
 — S3 50% 5min   
 — S3 20% 5min  
— S3 10% 5min 230V   
 — S3 10% 5min 400V

# MH 105






3000 rpm 230V 6000 rpm 400V



— S1 65K ΔT    — S3 50% 5min    — S3 20% 5min  
— S3 10% 5min 230V    — S3 10% 5min 400V

# MH 145






2500 rpm 230V 4500 rpm 400V



— S1 65K ΔT    — S3 50% 5min    — S3 20% 5min  
— S3 10% 5min 230V    — S3 10% 5min 400V

# MH 205

1700 rpm 230V 3000 rpm 400V




— S1 65K ΔT   
 — S3 50% 5min   
 — S3 20% 5min  
— S3 10% 5min 230V   
 — S3 10% 5min 400V

# MB 265

For MB 265 curves, please get in touch with our Technical Department


# Dimensions and Weight

## MH 56




Lenght	Brake	Feedback
LM	no	Resolver
LB	yes	Resolver
LE	no	SinCos
LBE	yes	SinCos

## MH 70 & MH 105



## MH 145 & 205



Servo motor	Type	LM/LB/LE/LBE	SF	IC	Flange	DF	F	D x L	b x h x i	t1	V x Z	QF	C x S		G	Weight
MH 56	0.2	130.5/181.5	6.5	40	5	5.5	63	9 x 20 11 x 23	3 x 3 x 16 4 x 4 x 18	10.2 12.5	--	56	Ø40	h6 x 2.5	74	0.7
	0.4	150.5/201.5														1.0
	0.6	170.5/221.5														1.3
MH 70	0.5	158/214/---/---	8.5	85	5	6	75	11 x 23 14 x 30	4 x 4 x 18 5 x 5 x 25	12.5 16.0	M4 x 10 M5 x 12.5	70	Ø60	h6 x 2.5	90	2.0
	01	188/244/---/---														2.8
	1.5	218/274/---/---														3.5
	02	248/304/---/---														4.3
MH 105 Flange B5/14	02	186/250/206/260	10	90	5 14	9.5 M8	115	19 x 40 24 x 50	6 x 6 x 30 8 x 7 x 40	21.5 27.0	M6 x 16 M8 x 19	105	Ø95	h6 x 3.5	140	5.0
	04 (02ML)	229/293/250/304														7.0
	06 (04 ML)	273/337/294/348														9.0
	08 (06 ML)	317/381/338/392														11.00
MH 105 Flange B6/9	02	186/250/206/260	10	90	6 9	9 7	130 100	19 x 40 24 x 50	6 x 6 x 30 8 x 7 x 40	21.5 27.0	M6 x 16 M8 x 19	116 96	Ø110 Ø80	h6 x 3.5 h6 x 3.5	155 128	5.0
	04 (02ML)	229/293/250/304														7.0
	06 (04 ML)	273/337/294/348														9.0
	08 (06 ML)	317/381/338/392														11.00

Servo motor	Type	LM/LB/LE/LBE	SF	IM	IC	Flange	DF	F	D x L	b x h x i	t1	V x Z	QF	C x S		G	Weight
MH 145	04	200/274/ 220/294	12	125	103	5 14	11.5 M10	165	24 x 50 28 x 60	8 x 7 x 40 8 x 7 x 50	27 31	M8 x 19 M10 x 22	145	Ø130	h6 x 3.5	200	8.0
	08 (04 ML)	231/305/ 251/325															12.0
	15 (08 ML)	292/366/ 312/396															18.0
	22 (15 ML)	354/428/ 374/448															23.0
	28 (22 ML)	416/490/ 436/510															28.0
MH 205	28	273/372/ 293*/392	18	172	132	5	14	215	38 x 80 42 x 110	10 x 8 x 70 12 x 8 x 100	41 45	M12 x 32 M16 x 40	205	Ø180	h6 x 4	250	29.0
	50 (28 ML)	342/441/ 362*/461*															44.0
	70 (50 ML)	411/510/ 431*/530*															59.0
	90 (70 ML)	480/579/ 500*/599*															74.0

mm for dimensions, kg for weight

\*applies only to SinCos Multiturn (Option A7), Option A6 (SinCos Singleturn) has no effect on the motor length.

For MB 265 dimensions please get in touch with our Technical Department

## Feedback Details

Code	Description
<b>Incremental encoder</b>	
A1	Incremental encoder 2000 i/t, 8 poles Precision $\pm 32''$ , Differential Line Driver 20 mA
A2	Incremental encoder 2048 i/t, 8 poles Precision $\pm 32''$ , Differential Line Driver 20 mA
A3	Incremental encoder 4096 i/t, 8 poles Precision $\pm 16''$ , Differential Line Driver 20 mA
B1	Incremental encoder 3000 i/t, 4 poles Precision $\pm 22''$ , Differential Line Driver 20 mA
B3	Incremental encoder 2048 i/t, 8 poles Precision $\pm 32''$ , Differential Line Driver 20 mA
B8	Incremental encoder 3000 i/t, 8 poles Precision $\pm 22''$ , Differential Line Driver 20 mA
C2	Incremental encoder 2048 i/t, 4 poles Precision $\pm 32''$ , Differential Line Driver 20 mA
<b>Absolute encoder Hiperface</b>	
C6	Single turn optical encoder, 1 Vpp, 128 sinusoid/t, Hiperface Protocol, 4096 positions/g Precision $\pm 320''$
C7	Single turn optical encoder, 1 Vpp, 128 sinusoid/t, Hiperface Protocol, 4096 positions/g, 4096 turns Precision $\pm 320''$
A6	Single turn optical encoder, 1 Vpp, 1024 sinusoid/t, Hiperface Protocol, 32 768 positions/g Precision $\pm 90''$
A7	Single turn optical encoder, 1 Vpp, 1024 sinusoid/t, Hiperface Protocol, 32 768 positions/g, 4096 turns Precision $\pm 90''$
<b>Absolute encoder EnDat</b>	
D5	Multiturn optical encoder, 1 Vpp, 512 sinusoid/t, EnDat Protocol, 8192 positions/t, 4096 turn Precision $\pm 60''$
B6	Single turn optical encoder, 1 Vpp, 2048 sinusoid/t, EnDat Protocol, 8192 positions/t Precision $\pm 20''$
C8	Multiturn optical encoder, 1 Vpp, 2048 sinusoid/t, EnDat Protocol, 8192 positions/t, 4096 turns Precision $\pm 20''$
C9	Single turn optical encoder, 1 Vpp, 32 sinusoid/t, EnDat Protocol, 131 072 positions/t Precision $\pm 400''$
B9	Multiturn optical encoder, 1 Vpp, 32 sinusoid/t, EnDat Protocol, 131 072 positions/t, 4096 turns Precision $\pm 400''$
F2	Multiturn optical encoder, 1 Vpp, 512 sinusoid/t, EnDat Protocol, 8192 positions/t, 4096 turn Precision $\pm 60''$
F3	Single turn optical encoder, 1 Vpp, 512 sinusoid/t, EnDat Protocol, 8192 positions/t, 4096 turn Precision $\pm 60''$

# Options

Code	Option description	Motor sizes					
		MH 56	MH 70	MH 105	MH 145	MH 205	MB 265
X	Increased Safety ATEX II 2G EEx and II T3 explosion proof in compliance with EN 60079-0 - EN 60079-7 - Directive 94/9/CE **			√	√		
A	Holding brake 24 VDC	√	√	√	√	√	√
V	Cooling - selfventilation			√	√	√	
SV	Cooling - servoventilation			√	√	√	
W	Cooling - water				√		
4	Flange B14			√	√		
5	Flange B5	√	√	√	√	√	√
6	Flange B6			√			
9	Flange B9			√			
S	Smooth shaft	√	√	√	√	√	√
2IB/2ID	Axial Interconnectron connectors Cables output front/back	√					
2I	Axial Interconnectron connectors Rotary cables output		√	√			
3I	Terminal box motor cables & Interconnectron connector feedback cable				√	√	
3	Form B3			√	√	√	
IP64	Protections	√	√	√	√	√	√
IP65 (optional)		√	√	√	√	√	√
B3/B1/B8/C2	Feedback		√	√			n.a.
C6/C7			√				n.a.
C9/D5/C8/B9/B6				√	√	√	n.a.
A6/A7				√	√	√	n.a.
F3/F2				√			n.a.
A1/A2/A3					√	√	√
M/ML	Increased inertia (middle inertia/high inertia)						
230 V	Supply voltage	√	√	√	√	√	
400 V		√	√	√	√	√	√

\*\* The certification is valid only if the motors are driven by HPD H3, with nominal currents from 2 to 16 A<sub>rms</sub> and supply voltage 400 V and motor derating

## Order Code MH / MB

M...	X	A	V	56	40	08	4	9	S	2ID	3	64	A1	M	2
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16

1	Motors family	MH / MB: Motor with resolver (integrated) ME: Encoder feedback (integrated)
2	Atex	X: Increased Safety ATEX II 2G EEx and II T3
3	Brake	A: Holding brake AM: Holding brake with increased braking
4	Ventilation	V: Selfventilation SV: Servoventilation W: Water cooling
5	Motor size	56/70/105/145/205/265
6	Nominal speed	[100 min <sup>-1</sup> ] - example 40 = 4000 min <sup>-1</sup>
7	Stall torque	65K (T <sub>065</sub> ) [Nm] - example 08 = 8 Nm
8	Flange	4: Flange B14 5: Flange B5 6: Flange B6 9: Flange B9
9	Shaft diameter	9/11/14/19/24/38 [mm]
10	Smooth shaft (without key)	S
11	Connectors	2IB/2ID: Axial Interconnectron connectors cables output front/back 2I: Axial Interconnectron connectors rotary cables output 3I: Terminal box & Interconnectron connector
12	Form	3: Form B3
13	Protections	64: IP64 65: IP65
14	Feedback	please see page with options
15	Inertia	M: Middle inertia ML: High inertia
16	Voltage supply	2: 230 V 4: 400 V

### STANDARDS

In compliance with: EN 60034-5, EN 60529, EN 60529/A1 Marked 







**WARNING – USER RESPONSIBILITY**

**FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.**

- This document and other information from Parker-Hannifin Corporation, its subsidiaries and authorized distributors provide product or system options for further investigation by users having technical expertise.
- The user, through its own analysis and testing, is solely responsible for making the final selection of the system and components and assuring that all performance, endurance, maintenance, safety and warning requirements of the application are met. The user must analyze all aspects of the application, follow applicable industry standards, and follow the information concerning the product in the current product catalog and in any other materials provided from Parker or its subsidiaries or authorized distributors.
- To the extent that Parker or its subsidiaries or authorized distributors provide component or system options based upon data or specifications provided by the user, the user is responsible for determining that such data and specifications are suitable and sufficient for all applications and reasonably foreseeable uses of the components or systems.

Additional information available on:

[www.parker-eme.com/smh](http://www.parker-eme.com/smh)

[www.parker-eme.com/smb](http://www.parker-eme.com/smb)

[www.parker-eme.com/mh](http://www.parker-eme.com/mh)

[www.parker-eme.com/mb](http://www.parker-eme.com/mb)



Parker Hannifin GmbH & Co. KG  
**Electromechanical Automation**  
Robert-Bosch-Straße 22  
D-77656 Offenburg, Germany  
☎ +49 (0)781 / 509-0  
📠 +49 (0)781 / 509-98176  
sales.automation@parker.com  
www.parker-eme.com

Parker Hannifin Spa  
**Electromechanical Automation**  
Via C. Gounod, 1  
I-20092 Cinisello Balsamo (MI), Italy  
☎ +39 02361081  
📠 +39 0236108400  
sales.automation@parker.com  
www.parker-eme.com