

5-HIGH LOADED CONTAINER FORKLIFT TRUCK Products Marketing



Product Information

Truck Model:	FD420
Equipment Code:	F-BZ5
Rated capacity(Kg):	25000/12500 (5-HIGH) 30500/9500(4-HIGH) 35000/6600(3-HIGH)
Maximum lift height(mm):	12500
Spreader type:	SPREADER
Load centre distance(mm):	1220
Maximum lift speed(mm/s):	200
Lowering speed with load(mm/s):	<600
Tilting angle forward/backward (deg):	3/3
Forward(Km/h):	1st 5.7 2nd 13.3 3rd 22.2 4th 34.3
Reverse(Km/h):	1st 5.7 2nd 13.3 3rd 22.2 4th 34.3
Minimum turning radius(mm):	7600
Gradeability (%):	10
Shift side(Every side)(mm):	
Overall length(mm):	10710
Overall width(mm):	6060
Overall height(mm):	TO TOP OF MAST LOWERED 9850 MAST EXTENDED 16100

	TO TOP OF OVERHEAD GUARD 5370
Wheel base(mm):	5500
Tread(mm):	FRONT 2650 REVERSE 2750
Stack:	5-HIGH
Under clearance(mm):	320
Engine:	MODEL MITSUBISHI 6D22TC DISPLACEMENT 11149cc RATED POWER/SPEED 220.5 Kw /2200 rpm MAX.TORQUE/ SPEED 1136.8/1400 rpm
Fork length(mm):	
Service weight(Kg):	70670
Tyre:	FRONT 4X18.00-25-36PR REAR 2X16.00-25-28PR
Transmission form:	HYDRAULIC
Oil:	DIESEL
Forklift truck stability:	CONFORM TO Q/DC.J.028-1996 STANDARD
Instruction:	