

CE FC

H.264

# *The new generation of H.264 DVR*



- *Dual Stream with more convenient web transmission*
- *120(100)fps Recording at Half D1 (4CH)*
- *Easy Control via Touch Screen Monitor, USB Mouse, Keyboard Controller*
- *4 Users + 1 Admin simultaneous View & Operation*
- *Mobile View on 3G Device*
- *Exactly the Same Interface as Local DVR for Remote Control (Client, IE Web Browser, Mobile)*
- *Multiple Remote Site Access & Control (CMS)*



4ch, 8ch, 16ch

Front View



Rear View



Specification

Model Name		4ch	8ch	16ch	
OPERATION SYS.		LINUX			
VIDEO	VIDEO SYSYEM	NTSC/PAL Switch Selectable	AUTO Detect	NTSC/PAL Switch Selectable	
	INPUT	BNC*4,1.0Vp-p,75ohm	BNC*8,1.0Vp-p,75ohm	BNC*16,1.0Vp-p,75ohm	
	CVBS	1CH, BNC			
	SPOT	1CH, BNC			
	LOOP OUT	without loop		BNC*16 with termination s/w	
	VGA OUTPUT	D-sub STANDARD			
AUDIO	INPUT	1CH,RCA	4CH,RCA	4CH,RCA	
	OUTPUT	1CH,RCA	2CH,RCA	1CH,RCA	
CONTROL	MOUSE	1*USB1.1 (Rear)			
	IR CONTROLLER	YES			
STORAGE	BUILD IN INTERFACE	SATA*2(2*HDD or 1*HDD+1*DVD±RW)		SATA*4(4*HDD or 2*HDD+1*DVD±RW)	
DISPLAY	DIVISION	1,4	1,4,8	1,4,9,16	
	ZOOM	2*~8*(Playback Zoom Support)2*			
RECORDING	COMPRESSION	H.264 Main Profile H.264			
	RECORDING MODE	Normal (Continue), Event, Schedule			
	RESOLUTION	NTSC	720*480,720*240,360*240		
		PAL	720*576,720*288,360*288		
	FRAME RATE	NTSC	120(HALF D1)FPS	240FPS	480FPS
PAL		100(HALF D1)FPS	200FPS	400FPS	
QUALITY	Highest,High,Normal,Basic,Below Basic				
MOTION DETECTION	Sensitivity:10Level,22*15Grid				
WATER MARK	YES				
PLAYBACK	FRAME RATE	120(100)FPS			
	SPEED	Normal,REW&FF(1/4,1/2,2*,4*,8*,16*,32*,64*)			
	SEARCH METHOD	Event,Time(Calendar)			
COMMUNICATION	REMOTE SOFTWARE	Remote Client, IE Brower, Mobile, CMS			
	REMOTE OPERATION	Virtual DVR-Same As Local OSD			
	NETWORK SERVICE	TCP/IP,HTTP,DDNS,SMTP(SSL)			
	3G DEVICE	ADSL,LAN,DHCP			
	GUI INTERFACE	Win Mobile5.0,6.0, Symbian, PDA, Blackberry, Iphone(recommended)			
BACKUP	EXTERNAL	Supported GUI 32 Bit True Color			
	NETWORK	Pelco P/PelcoD/KND/LiLin/LG/Samsung/AVTECH			
	FILE	DVD±RW			
GENERAL	ALARM IN/OUT	4 / 1	8 / 1	16 / 2	
	RS-485	1	1	1	
	UNIT DIMENSION(mm)	380(W) * 350(D) * 73(H)			
	RECOVERY	Watchdog			
	OPERATION TEMPTERATURE	-5°C ~ 40 °C			
POWER CONSUMPTION	DC 12V,5A,60W		DC 12V,7A,84W		

\*Specification could be change without notice

System Diagram

