

REMEMBER TO GET
A QUOTE ON
OPTIONS

AVAILABLE IN
STAINLESS
STEEL EXTERIOR

-30/+10°C

LABORATORY REFRIGERATORS AND FREEZERS

LR/LF series

LR (Laboratory Refrigerator) LF (Laboratory Freezer)

LR/LF series

- White or stainless steel exterior
- Stainless steel interior
- Automatic door closing
- Air forced cooling
- Adjustable shelves
- Castors
- Door key lock
- Reversible door

Controller features

- Micro processor controller with digital display
- Approx. 72 hours battery back up for alarms, loggings and temperature display in case of power cut
- Visual and acoustic alarm
- Adjustable high/low temperature alarm
- Power failure alarm
- Probe failure alarm
- Instrument failure alarm
- Open door alarm
- Contact for remote alarm
- Prepared for GSM alarm
- Integrated data logger (software included)
- RS485/232 Interface
- Computer USB data read out
- Auto cycle if probe failure
- Ambient temperature display
- Stows all alarms
- Direct download/upload on/ from USB memory stick
- 3-level password protected
- Battery level indication
- Integrated memory

Unite the latest technologies in one refrigerator: the Arctiko laboratory line is produced with attention to details and is user friendly. The LR and LF range has many features and unit sizes to offer, but no matter which product you choose, it is built after the same strict guidelines.



LR/LF 500



LR/LF 1400



LR/LF 700



Micro processor controller with digital display.

Model	LR 300 **	LF 300**	LR 500**	LF 500**
Item code (DAI no.)	DAI 0220/0221*	DAI 0225/0226*	DAI 0240/0241*	DAI 0245/0246*
Dimensions exterior WxDxH (mm)	520x700x1997	520x700x1997	620x860x1997	620x860x1997
Net capacity (L)	345	345	515	515
Temperature range (°C)	+1/+10	-30/-10	+1/+10	-30/-10
Power supply (V)	230	230	230	230
Frequency (Hz)	50	50	50	50
Model	LR 700**	LF 700**	LR 1400**	LF 1400**
Item code (DAI no.)	DAI 0250/0251*	DAI 0255/0256*	DAI 0270/0271*	DAI 0275/0276*
Dimensions exterior WxDxH (mm)	720x860x1997	720x860x1997	1440x860x1997	1440x860x1997
Net capacity (L)	615	615	1240	1240
Temperature range (°C)	+1/+10	-30/-10	+1/+10	-30/-10
Power supply (V)	230	230	230	230
Frequency (Hz)	50	50	50	50

We reserve the right to change specifications without notice. Subject to confirmation and availability.

* DAI number for unit with stainless steel exterior. ** For stainless steel exterior please add -ST to the existing product name.

Scan me and see more
about LEF 270



www.arctiko.com