

Further Models



Z 233 M-2

Order number:

50-60 Hz / 120 V 282.00 V31
50-60 Hz / 230 V 282.00 V30

Aircooled Microcentrifuge

Brushless Motor
LED display for speed / RCF and running time
„Quick“- key for short runs
Electrical lid lock
Speed regulation 250 - 15000 rpm in increments of 250 rpm
Time regulation 1 - 60 min in increments of 1 min or cont.

Technical Data

max. Speed:	15000 min-1	Dimensions (WxHxD):	28 x 29 x 55 cm
max RCF:	21380 xg	Weight:	16 kg
max. Noise level:	57 dBA	Power consumption:	230 W
		Package:	38 x 38 x 48 cm / 17 kg



Z 160 M

Order number:

50-60 Hz / 120 V 290.00 P02 cpl. with rotor 220.95 V04
50-60 Hz / 230 V 290.00 P01 cpl. with rotor 220.95 V04

Aircooled Microcentrifuge

Brushless motor
Electrical lid lock
Speed regulation 1000 - 14000 rpm
Time regulation 1 - 30 min in increments of 1min or cont.
„Quick“- key for short runs

Technical Data

max. Speed:	14000 min-1	Dimensions (WxHxD):	20 x 18 x 22 cm
max RCF:	15996 xg	Weight:	4,5 kg
max. Noise level:	57 dBA	Power consumption:	120 W
		Package:	31 x 25 x 31 cm / 6,5 kg



Z 100 M

Order number:

50-60 Hz / 120 V 292.00 P02
50-60 Hz / 230 V 292.00 P01

„Personal“- Microcentrifuge

Technical Data

max. Speed:	6000 min-1	Dimensions (WxHxD):	15 x 10 x 15 cm
max RCF:	2000 xg	Weight:	0,9 kg
max. Volume:	6 x 1,5/2,0 ml	Package:	24 x 17 x 15 cm / 1,1 kg

Extend of Supply

Unit incl. rotor for 6 x 1,5/2,0 ml, adapter 0,5 ml und 0,2 ml
incl. rotor for 2 x PCR strips

More from HERMLE:



COMPACT CENTRIFUGE **2206A**



HERMLE Labortechnik GmbH

Siemensstraße 25
78564 Wehingen • Germany

Phone: + 49 7426/9622-50

Telefax: + 49 7426/9622-49

E-Mail: vertrieb@hermle-labortechnik.de

Web: www.hermle-labortechnik.de

