

DO30

Dissolved Oxygen Tester

2014
New
Model



Precision easy operation: all functions operated in one hand.

Large LCD with backlight, Multi-line display for easy reading,
Auto-Power Off saves battery after 5 mins non-use.

1*1.5V AAA long battery life

Easy maintenance, simple to change battery and electrode

Floats on water, IP67 rated

Field throw measurement (Auto Lock Function)



CLEAN DO30 Dissolved Oxygen Tester

- Unit display: ppm or %.
- Automatically compensates salinity / barometric after manual input for increased accuracy.
- User replaceable membrane cap (CS49303H1L).

Characterized by the accuracy, economic, easy operation and maintenance, DO30 Dissolved Oxygen Tester offers you the best value dissolve oxygen measurements experiences.

Package Sets



DO30A

MDO30 Tester + CS4930 sensor + 1*1.5V AAA Electrode

Package Dimension: L*W*H 210*100*65mm
Weight : 350g

Range	0.00 - 20.00 ppm; 0.0 - 200.0%
Resolution	0.01 ppm ; 0.1%
Accuracy	±2% F.S.
Temp. Range	0 - 100.0 °C / 32 - 212 °F
Working Temperature	0 - 60.0 °C / 32 - 140 °F
Auto Temp. Compensation	0 - 60°C
Calibration	1 or 2 point auto calibrate (0% zero oxygen or 100% in air)
Salinity Compensation	0.0 - 40.0 ppt
Atmospheric Pressure Compensation	600 - 1100 mbar
Auto backlight off	1 minutes
Auto power off	5 minutes without key be pressed
Power	1x1.5V AAA battery
Dimensions	(H×W×D) 185×40×48 mm
Weight	95g
Protection	IP67



www.cleaninst.com
Water Analysis Solutions