

CON30

Conductivity Tester

(Conductivity / TDS / Salinity)

2014
New
Model



Precision easy operation: all functions operated in one hand.

Large LCD with backlight, Multi-line display for easy reading,
Auto-Power Off saves battery after 5 mins non-use.

1*1.5V AAA long battery life

Easy maintenance, simple to change battery and electrode

Floats on water, IP67 rated

Field throw measurement (Auto Lock Function)



CON30 is the best value salt meter in your pocket, with 4 parameters (Conductivity / TDS / Salinity / TEMP tester) in one and easy calibration. This dip-style tester is ideal for spot checking with greater flexibility.

Package Sets

CON30A MCON30 Tester + CS3930 sensor + 1*1.5V AAA Electrode



Package Dimension: L*W*H 210*100*65mm
Weight : 350g



www.cleaninst.com
Water Analysis Solutions

CLEAN CON30 Conductivity Tester

- Broad measuring range: 0-50.0mS/cm, from pure water to waste water applications.
- 4 parameters in one meter, simple calibration.

Range	0 - 200.0 , 2000 μ S/cm (ppm) , 0 - 20.00 , 50.0 mS/cm (ppt)
Resolution	0.1 , 1 μ S/cm (ppm) 0.01 , 0.1 mS/cm (ppt)
Accuracy	$\pm 1\%$ F.S.
Temp. Measuring Range	0 - 60 $^{\circ}$ C (32 - 140 $^{\circ}$ F)
Temp. Compensation Range	0.0 - 60.0 $^{\circ}$ C
Temp. Compensation Type	Auto/Manual
Solution Temp. Coefficient	0.00 - 10.00% (default 2.00%)
Reference Temp.	15.0 - 30.0 $^{\circ}$ C (default 25 $^{\circ}$ C)
Calibration	Any 1 Point Calibration
TDS Coefficient	0.40 - 1.00 Adjustable
Salinity Coefficient	0.65
Probe	CS3931 Graphite , K=1.0
LCD	20 * 30 mm multi-line crystal display
Protection	IP67
Auto backlight off	30 Seconds
Auto power off	5 minutes without key be pressed
Power	1*1.5V AAA battery
Dimensions	(H×W×D) 185×40×48 mm
Weight	95 g