

## Range of teeth, adapters and shrouds



### E

**Extra**  
For large excavators in highly abrasive applications requiring good penetration. Sizes available: 120, 180, 240 and 500.



### V

**Vector**  
For large excavators working in very compacted terrain guaranteeing maximum penetration. Sizes available: 120, 180, 240 and 500.



### P

**Penetration**  
For large excavators in compacted terrain that require a high degree of penetration and excellent resistance. Sizes available: 120, 180, 240 and 500.



### I

**Impact**  
For large excavators and loaders on terrain with a high degree of impact guaranteeing maximum resistance. Sizes available: 120 y 180.



### H

**Heavy**  
For loaders where there is a lot of abrasion. Sizes available: 120, 180 and 240.



### WC

**Weld center**  
For large excavators and loaders on sites which require high resistance on impact and abrasion. Sizes available: 120, 180, 240 and 500. For blade thicknesses from 64 to 140mm / from 2,5" to 5,5".



### M

**Mechanical shroud**  
Protects the top of the adapter from wear in high abrasion and impact applications.



### MTGtwist Locking System

Innovative locking solution without hammer consisting of a pin and elastomer and polyurethane retainer. Sizes available: 120, 180, 240 and 500.



### Extraction tool

Standard size square headed extraction tool