

All weldable MTG parts have a special grey coating which does not give off toxic gases and does not have to be removed prior to welding.



FC

Flush Central

For loaders in cleaning jobs where the terrain surface must be left smooth.
Sizes available: 5, 8, 10, 15, 20, 30, 40, 55, 65 and 80.



WL/WR

Weld left-right

For the corners of the excavator bucket.
Sizes available: from 15 to 55.

WL

WR



BC

Bolt on Central

For loaders in multiple applications and changing conditions.
Sizes available: 15, 20 and 30.



FCC

Flush central clamshell

For clamshell buckets.
Sizes available: 10, 15, 20 and 30.



BLR

BL

BR



BL/BR/BLR

Bolt on left-right

For loaders in multiple applications and changing conditions.
Sizes available BL/BR: 15, 20 and 30.
Sizes available BLR: 15 and 20.



WN/WN HS

Weld on nose

For applications in dragging or ripping. It is also very useful for repairing or converting any adapter to the system MTG Systems KingMet.
Sizes available: from 8 to 20 standard; and from 30 to 125 also for hot slag.



UC

Universal central

For mini and combined excavators in applications requiring little impact.
Sizes available: 5, 8, 10, 15, 20 and 30.



WC HS/FC HS

Weld Center Hot Slag

For loaders in applications with hot slag.
Sizes available WC HS: 55, 65 and 125.
Sizes available FC HS: 30, 40 and 65.

WC HS

FC HS



WC

Weld center

For excavators and loaders in hard work with abrasion, thanks to better blade fixation and excellent bucket protection.
Sizes available: from 8 to 250.



CL

Cast lips

For standard and hard applications. Available in 321, 470 and 622 mm blade lengths.
Offers optimum resistance and operating length.
Available with 3, 4 and 5 adapters.



WLD/WRD

Weld left-right delta blade/

Adapters for delta blade, for excavators and loaders.
Sizes available: from 55 to 250.



1

2

3

MTG Systems KingMet Locking Systems

1. Standard locking.
2. Hot slag locking.
3. Metal retainer.
Sizes available: 1 and 3; from 5 to 250 2: 30, 40, 55, 65 and 125.



WC HD

Weld center/Heavy duty with mechanical Wear cap

For excavators in applications with extreme abrasion.
Protects the top of the adapter from wear.
Sizes available: 55, 65, 80, 125, 200 and 250.



1

2

KingMet MTG Systems Extractors

1. Standard.
Sizes available: from 5 up to 250.
2. With glass fibre shaft.
Sizes available: 55, 65, 80, 125, 200 and 250.