



AR26

Compaction of in-situ concrete



Quality exposed concrete surface is king: A case for the AR 26

First-class compacted concrete is essential for the production of concrete surfaces. Thanks to its high-quality design, Wacker Neuson's external vibrator AR 26 offers this precision compaction. The result: Beautifully smooth and level concrete surfaces on walls, pillars and columns.

- Long staying power thanks to its powerful electric motor with stable speeds.
- Available for all standard voltages and frequencies
- Fast assembly thanks to easy to use fastening clamps
- Ca. 2 kg lighter than its forerunner model AR 36.
- Small, compact and light.



Also available with a practical ON/OFF switch.

Technical specifications

	AR 26/6/042	AR 26/6/042 cs	AR 26/6/042 3.5 kN
Vibrations rpm	6,000	6,000	6,000
Standard centrifugal force kN	2.17	2.17	3.47



	AR 26/6/042	AR 26/6/042 cs	AR 26/6/042 3.5 kN
Centrifugal force max. kN	3.47	3.47	3.47
Rated voltage 3~ V	42	42	42
Rated current A	8	8	8
Weight kg	6.26	7.34	6.46
L x W x H mm	223 x 190 x 102	223 x 190 x 102	223 x 190 x 102
Fastening	90 x 125	90 x 125	90 x 125

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions.

Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2016 Wacker Neuson SE.