



**WACKER
NEUSON**
all it takes!

CRT36

Ride-on Trowels



The best choice for finishing concrete surfaces: CRT36

Ride-on trowels of the CRT36 series have a diameter of 2 x 915 mm and are characterized by a high level of productivity and operating comfort. The practical, built-in wheel set can easily be operated from the back side by one person. There are no additional bothersome operator's controls on the front side. As a result, the end user has more freedom when using the machine.

- Optimum maneuverability thanks to its balanced power-to-weight ratio
- Sensitive, ergonomically designed 2-lever controls
- Variable coupling: For constant engine torque at low and high rotor speeds
- Good visibility thanks to front and rear lights as standard – especially on night operations



Integrated wheel set

Simpler and faster blade replacement, thanks to the integrated wheel set.

Technical specifications



	CRT36-25	CRT36-26A
L x W x H Shipping mm	2,032 x 1,041 x 1,372	2,032 x 1,041 x 1,372
Operating weight kg	454	451
Blades and finishing data		
Troweling diameter mm	915	915
Quantity of blades	8	8
Blades mm	355 x 152	355 x 152
Combination blades mm	355 x 203	355 x 203
Combination blades mm	355 x 254	355 x 254
Pitch range °	0 - 25	0 - 25
RPM Area rpm	25 - 165	25 - 165
Engine / Motor		
Engine / Motor	Air-cooled, two-cylinder, four-cycle gasoline engine	Air-cooled, two-cylinder, four-cycle gasoline engine
Engine / Motor manufacturer	Wacker Neuson	Honda
Displacement cm³	720	688
Operating performance kW (hp)	18.7 (25)	16.4 (22)
RPM / speed Operating rpm	3,600	3,600
Fuel type	Unleaded Gasoline	Unleaded Gasoline
Fuel consumption l/h	9	9
Tank capacity Fuel l	24.6	24.6

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions.

Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2016 Wacker Neuson SE.