

Safe

Heating and Mixing



Leading Safety Standards

Superior Ease of Use

Reduced Cost of Ownership

 **heidolph**
research made easy




Have you ever heard of hotplates with fast heat-up times and chemical resistance?

Safe Heating and Mixing

The unique Kera-Disk® heating plate of aluminum provides fast heating times, and the wafer-thin ceramic coating makes the heating plate both chemically and scratch resistant!

Leading Safety Standards

- To prevent accidents or laboratory fires, all magnetic stirrers feature **two independent safety circuits** which switch off heating in case of any overtemperature situation
- In combination with Heat-On attachments you can convert your lab into a **"safety zone"**
- Hotplate **residual heat indicator** in the digital display of the MR Hei-End is illuminated when unit is turned off and hotplate temperature is above 50 °C to warn operator of potential burn hazards
- For your safety, the **unit will power off** in case of a short-circuit, a damage to the temperature sensor, a motor failure or other incidences during operation
- To protect you from splashes and scalding from bath media, rotation speed **ramps up slowly** until unit has reached the pre-programmed speed
- A separate on/off switch for heating **prevents unintentional heat-up.** If heating is switched on, the on/off button is illuminated for visual control
- Even if the stirrer is exposed to the highest temperatures, damage is categorically ruled out – all models come with a **fire-resistant aluminum die-cast housing**






Reduced Cost of Ownership

- **Reduce your process times!** The extended heating capacity of 800 W reduces your heat-up time by 35 % compared to other units at 600 W
- The **hermetically-sealed housing** protects all mechanical and electronic components from aggressive environments
- The maintenance-free non-sparking motors **reduce down times**
- The design and features give an **increased lifespan of 10 years** along with significantly **reduced maintenance and repair costs**

Superior Ease of Use

- All units with digital display allow for easy setting and monitoring values on the **illuminated readout**
- You can even **work with dry ice** – a robust thermal insulation prevents corrosion inside the housing by preventing condensate from collecting and dripping on any electronic components
- An optional software program is available for the MR Hei-End to aid you in automating your process, and **saves all data in electronic files**
- The strong magnetic field allows for **easy stirring** of even higher **viscosity media**
- The unique Kera-Disk® coating is extremely chemical-resistant and scratch-proof and can be **cleaned easily** if solvents, oil or other contaminations are spilled on the plate
- The chemically resistant Kera-Disk® hot plate allows for **immediate heat transfer** resulting in quick heat-up times
- In case the heating function fails, stirring will not be discontinued to **avoid thermal damage** to your sample



Safe Heating and Mixing

Leading Safety Standards

Superior Ease of Use

Reduced Cost of Ownership

› Kera-Disk® top plate

With Kera-Disk® material coating, fast heat-up times and chemical resistance!




YOUR ADVANTAGES

- Glass ceramic top plates offer the benefits of chemical and scratch resistance but produce longer heat-up times
- Aluminum top plates allow for immediate heat transfer but are not chemical-resistant or scratch-proof
- Kera-Disk® top plates take the best of two worlds: The aluminum top plate allows for immediate heat transfer for quick heat-up times and a thin layer of ceramic coating makes the top plate chemical-resistant and scratch-proof

› Sealed housing

The sealed housing of the MR series guarantees extended performance life and reduced maintenance!



YOUR ADVANTAGES

- Protection against aggressive fumes, liquids and vapors which prevents internal corrosion. This results in an increased lifespan of 10 years on average at reduced maintenance and repair cost
- Protection of all mechanical and electronic components against aggressive environmental conditions

The hermetically-sealed housing that protects the PC board and the motor is marked in black. The way a liquid would take flowing down from the hotplate is marked in orange. As one can see, even if the liquid reaches the heat shields, it cannot ingress to the PC board and the

motor but is drained off. The other line marked in orange shows that gas can neither ingress to the PC board nor to the motor. The apparent gap is due to temperature insulation. Because of that gap the temperature inside the magnetic stirrer stays substantially lower, which

significantly increases the durability of the magnetic stirrer. For protection against liquid and gas, the heating elements are completely embedded in ceramic.

The average operational **lifespan of 10 years** is backed by a **3 year warranty** and makes your purchase a worthwhile investment.

The extended heating capacity of **800 W** reduces heat-up times by **35 %** compared to other units at 600 W

Hermetically-sealed housing **protects** all mechanical and electronic components **from aggressive environments**

The chemically resistant Kera-Disk® hot plate allows for **immediate heat transfer** resulting in quick heat-up times

In case the heating function fails, stirring will not be discontinued to **prevent bumping**



The temperature sensor consists of **two independent safety circuits** which switches off heating in case of any overtemperature situation

In case of a short-circuit, a damage or removal of the temperature sensor from the media, the **unit powers off completely**

Damage to the stirrer is categorically ruled out even if exposed to highest temperatures – all models come with **a fire-resistant aluminum die-cast housing**

A separate on/off button for heating **prevents unintentional heat-up** – the button is illuminated for visual control

➤ Magnetic Stirring Hotplates

Preferred use of the MR Series magnetic stirrers includes smooth to intense mixing and heating of low-viscosity fluids. Your first choice for decomposing organic and inorganic substances

- With a heating power of 800 W the hotplate reaches a maximum temperature of 300 °C in a significantly reduced time period
- Safety circuits avoid an overheat situation of your hotplate: if the temperature overshoots the heating will be powered off immediately
- The strong magnetic field allows for stirring even higher viscosity media or volumes of 20 liters of water with ease
- Speed is adjustable from 30 respectively 100 to 1,400 rpm at an accuracy of up to $\pm 1\%$ for gentle mixing

For standard applications without temperature sensor



MR Hei-Standard

For higher requirements with temperature sensor



MR Hei-Tec with Pt 1000

For highest safety



MR Hei-End with Pt 1000

The StarFish system can convert your magnetic stirrer over to a time-saving multiple-reaction workstation



StarFish system

The Heat-On attachments are the industry's safest, fastest and most time-efficient method to heat and stir a sample in a round-bottom flask



Heat-On system

➤ MR Hei-Standard

Model for standard applications without temperature sensor

The MR Hei-Standard includes all leading safety standards and features for superior ease of use and reduced cost of ownership, plus:

- For your protection an independent safety circuit will switch off heating if hotplate temperature exceeds 25 °C over set temperature
- A separate on/off switch for heating prevents an unintentional heat-up. If heating is switched on the on/off button is illuminated for visual control
- Analog knobs allow for convenient speed setting from 100 to 1,400 rpm at an accuracy of $\pm 2\%$ and temperature setting up to 300 °C



MR Hei-Standard
P/N 505-20000-00

➤ MR Hei-Tec

Model for higher requirements with temperature sensor

The MR Hei-Tec includes all leading safety standards and features for superior ease of use and reduced cost of ownership, plus:

- This unit features a digital display and allows for easy setting and monitoring of values in the illuminated readout
- For your protection an independent safety circuit will switch off heating if hotplate temperature exceeds 25 °C over set temperature
- Digital speed setting from 100 to 1,400 rpm at an accuracy of $\pm 2\%$ and temperature setting up to 300 °C
- A separate on/off switch for heating prevents an unintentional heat-up. If heating is switched on the on/off button is illuminated for visual control
- An illuminated button indicates clearly if the stirring mode is activated
- Upgrade this magnetic stirrer with the optional Pt 1000 temperature sensor for precise temperature control, overshoot protection and reproducible results

MR Hei-Tec
P/N 505-30000-00

MR Hei-Tec with Pt 1000
P/N 505-30081-00



MR Hei-End

Model for highest safety

The MR Hei-End includes all leading safety standards and features for superior ease of use and reduced cost of ownership, plus:

- An independent safety circuit switches off heating at an operator-programmed temperature value above your set temperature
- An additional operational safety step is required to change parameters which prevents unwanted changes to the actual setting
- The digital display allows for easy setting and monitoring of values on the illuminated readout. Speed setting from 30 to 1,400 rpm at an accuracy of $\pm 1\%$ and temperature setting up to 300 °C
- Hotplate residual heat indicator in the digital display illuminates when unit is turned off and hotplate temperature is above 50 °C to prevent accidental operator injury
- To protect your sample from overheating a safety circuit switches off heating if the temperature sensor is not immersed in your media vessel
- A separate on/off switch for heating prevents an unintentional heat-up. If heating is switched on the on/off button is illuminated for visual control
- Upgrade this magnetic stirrer with the optional Pt 1000 temperature sensor for precise temperature control, overshoot protection and reproducible results



MR Hei-End
P/N 505-50000-00

MR Hei-End with Pt 1000
P/N 505-50081-00

Software Hei-PC-Control


- Utilize the optional software to control and document the entire process
- MR Hei-End features a digital RS 232 and analog interface for connecting the optional software easily



Hei-PC-Control Software for MR Hei-End
P/N 592-50500-00

Heat-up graph

- Take advantage of a built-in PID controller that ensures fastest heat-up times while preventing an overtemperature situation of your sample



Accessories



1-l Heating bath
PTFE-coated
P/N 504-93100-00



2-l Heating bath
PTFE-coated
P/N 504-92100-00



4-l Heating bath
PTFE-coated
P/N 504-91100-00



Concave block adaptor
For 1-l round-bottom flasks
P/N 504-94000-00



1-l Heating bath for oil
Max. temperature 250 °C
P/N 504-93000-00



2-l Heating bath for oil
Max. temperature 250 °C
P/N 504-92000-00



4-l Heating bath for oil
Max. temperature 250 °C
P/N 504-91000-00



Pt 1000 clamping system
(includes support rod and attachment with cable inlet)
P/N 509-63100-00
Pt 1000 clamping system for bath attachments from 3 to 5 liter
(includes support rod and attachment with cable inlet)
P/N 509-63200-00



Silicone protective cover
Replaceable cover against splashes and dripping water

For MR Hei-Tec and MR Hei-End
P/N 23-07-06-05-59
For MR Hei-Standard
P/N 23-07-06-05-63



Pt 1000 temperature sensor glass-coated
For MR Hei-End, MR Hei-Standard and MR Hei-Tec
P/N 509-67920-00

Pt 1000 temperature sensor stainless steel
For MR Hei-End, MR Hei-Standard and MR Hei-Tec
P/N 509-67910-00



Holding device MR
For safe fixation on lab frames to gain extra lab space. Comes with clamp as standard
P/N 509-96000-00

Stirring bars

| | P/N |
|--|--------------|
| Stirring bars - cylindrical shape (25, 40, 50 mm each) | 509-56000-00 |
| Stirring bars - cross shape (16.5 mm) pack of 20 pcs. for 25-ml to 50-ml flasks | 509-58500-00 |
| Stirring bars Evaluation Kit pack of 10 pcs. | 509-58300-00 |
| Stirring bars - oval shape (15x6 mm) pack of 3 pcs. for 10-ml flasks | 509-53000-00 |
| Stirring bars - oval shape (25x10 mm) pack of 3 pcs. for 25-ml to 50-ml flasks | 509-54000-00 |
| Stirring bars - oval shape (30x10 mm) pack of 3 pcs. for 100-ml to 250-ml flasks | 509-55000-00 |

Heat-On Attachments

The Heat-On attachments are suitable to replace oil baths and heating mantles in your lab and reduce the risk of fire hazards. Moreover the attachments minimize the messy oil clean-ups that result from changing oil or removing flasks from an oil bath!

- Our attachments are by far the safest, fastest and most efficient method for heating and mixing solutions in round-bottom flasks from 10 ml to 5 liter
- Heat-On fits precisely to every flask, thus ensuring maximum surface contact and fast heat transfer. Eliminates the mess from cleaning flasks after removal from an oil bath or hazardous spills when an oil bath slips off a stirring plate. As a result, oil as a heat transfer media is made redundant and your lab is a safer place with the Heat-On block system



| Flask volume | Volume of water | Hotplate temperature | Time to reach boiling |
|--------------|-----------------|----------------------|-----------------------|
| 10 ml | 6 ml | 300 °C | 6.8 min |
| 25 ml | 15 ml | 300 °C | 8.0 min |
| 50 ml | 30 ml | 300 °C | 8.5 min |
| 100 ml | 60 ml | 300 °C | 8.8 min |
| 150 ml | 100 ml | 300 °C | 10.0 min |
| 250 ml | 150 ml | 300 °C | 10.8 min |
| 500 ml | 300 ml | 300 °C | 16.4 min |
| 1,000 ml | 600 ml | 300 °C | 21.1 min |
| 2,000 ml | 1,200 ml | 300 °C | 35.1 min |
| 3,000 ml | 1,800 ml | 300 °C | 47.3 min |
| 4,000 ml | 2,400 ml | 300 °C | 51.0 min |
| 5,000 ml | 3,000 ml | 300 °C | 75.5 min |

Leading Safety Standards

- Prevents accidents, fires and contamination by completely banning all oil baths from your laboratory
- This unique design prevents glass breakage and protects you from spilled chemicals or solvents
- The high temperature range provides unlimited safety for applications up to 260 °C

Superior Ease of Use

- A unique PTFE-coating on the aluminum Heat-On body allows for superior chemical resistance and many years of service life
- Precise temperature control inside the vessel or on the heating block with a thermocouple port that provides actual block temperature back to your MR series hotplate

Reduced Cost of Ownership

- Increase your daily work throughput significantly and reduce your overall process times by quick changing of Heat-On blocks
- Save energy costs – 1,000 ml of water heats up 66 % faster than conventional oil baths
- 150 ml of water boils in less than 11 minutes

Heat-On Attachments

Heat-On blocks

Each Heat-On block is a stand-alone product that can be placed directly onto the stirring hotplate

- Heat-On 250-ml block** 505-80067-00
- Heat-On 250-ml block with flask sidearm cutouts** 505-80067-01
- Heat-On 500-ml block** 505-80069-00
- Heat-On 1-l block** 505-80071-00
- Heat-On 2-l block** 505-80073-00
- Heat-On 3-l block** 505-80075-00
- Heat-On 4-l block** 505-80078-00
- Heat-On 5-l block** 505-80076-00



Heat-On 250-ml block with flask sidearm cutouts



Heat-On 2-l block

Heat-On accessories

- Support rod for bath attachments from 3 to 5 liter** 509-97000-00
- Retort clamp** 505-81075-00
- Boss head** 570-31100-00
- Flask Stand & Clamp Kit (including Support rod for bath attachments from 3 to 5 liter, Retort clamp, Boss head)** 505-81400-00

PTFE Safety Covers*

- For Heat-On Multi-Well holder** 505-80080-00
- For Heat-On 200-300-ml block** 505-80081-00
- For Heat-On 500-ml block** 505-80082-00
- For Heat-On 1-l block** 505-80083-00



PTFE safety covers



PTFE safety cover 500 ml

* Not available in the USA

Multi-Well holder and inserts

This unique Multi-Well holder is designed to hold either one or two inserts for flasks*.

The inserts are available for 10-ml, 25-ml, 50-ml, 100-ml and 150-ml flasks. Flask inserts also feature cut-away sides for use with two or three-neck flasks and accept the optional safety lifting handles

* Only accepts one 150-ml insert



Heat-On Multi-Well holder P/N 505-80060-00

Heat-On safety lifting handles P/N 505-80077-00

Insert for Multi-Well holder

- Heat-On 10-ml insert** 505-80061-00
- Heat-On 25-ml insert** 505-80062-00
- Heat-On 50-ml insert** 505-80063-00
- Heat-On 100-ml insert** 505-80064-00
- Heat-On 150-ml insert** 505-80065-00



Heat-On 10-ml insert



Heat-On 50-ml insert

Heat-On Multi-Well packages

- Package Heat-On Multi-Well Basic** 505-81300-00
Including 1x Multi-Well holder and 3 inserts for 25-ml, 50-ml and 100-ml flasks

- Package Heat-On Multi-Well** 505-81200-00
Including 1x Multi-Well holder and 6 inserts, 2 each for 25-ml, 50-ml and 100-ml flasks

StarFish Workstations

Have you always been looking for a system to perform numerous reactions on a small footprint to significantly reduce space and process times?

With our attachments you can turn your magnetic stirrer into an efficiency-increasing reaction station for up to 45 samples simultaneously!

- Upgrade your magnetic stirrer to a product with multiple capabilities
- No special glassware purchase required - use your own glassware and cherry-pick the appropriate attachments for your applications
- Starting from simple heating and mixing tasks including chemical reactions, concentrations, extractions under vacuum and by providing protective gas
- StarFish workstations are ideal for soxhlet applications



Base plate

Base plate with optional handles fits securely onto the top plate maintaining good thermal contact with the heated surface

StarFish base plate (145 mm)
505-81000-00

StarFish base plate handles (pair)
505-81001-00



MonoBlocks

MonoBlocks are single blocks with multiple wells all of the same size and are ideal for experiments using the same vessel

MonoBlock for 5 x 250-ml flasks 505-80001-00

Inserts for MonoBlock 5 x 250 ml

150-ml Flask insert 505-80040-00
100-ml Flask insert 505-80041-00
50-ml Flask insert 505-80042-00
25-ml Flask insert 505-80043-00
10-ml Flask insert 505-80044-00
5-ml Flask insert 505-80045-00

MonoBlock for 16 x 25-mm tubes 505-80002-00
MonoBlock for 16 x 24-mm tubes 505-80003-00
MonoBlock for 40 x 16-mm tubes 505-80004-00
MonoBlock for 40 x 12-mm tubes 505-80005-00

MonoBlock for 16 x 28-mm vials 505-80006-00
MonoBlock for 20 x 21-mm vials 505-80007-00
MonoBlock for 40 x 17-mm vials 505-80008-00
MonoBlock for 40 x 15-mm vials 505-80009-00
MonoBlock for 40 x 12-mm vials 505-80010-00

Numerous combinations

Cherry-pick from different PolyBlock options in different sizes or one MonoBlock system for identical round-bottom flasks or vials. In addition, you can choose from a large selection of inserts ranging from 5 ml to 150 ml

PolyBlocks

PolyBlocks are smaller segments (5 per StarFish) which can be mixed to accommodate any combination of vessels; allowing the use of different vessel types and sizes at the same time

PolyBlock for 1 x 250-ml flask 505-80020-00

PolyBlock for 3 x 25-mm tubes 505-80021-00

PolyBlock for 3 x 24-mm tubes 505-80022-00

PolyBlock for 9 x 16-mm tubes 505-80023-00

PolyBlock for 9 x 12-mm tubes 505-80024-00

PolyBlock for 3 x 28-mm vials 505-80025-00

PolyBlock for 3 x 21-mm vials 505-80026-00

PolyBlock for 7 x 17-mm vials 505-80027-00

PolyBlock for 9 x 15-mm vials 505-80028-00

PolyBlock for 9 x 12-mm vials 505-80029-00



5-way clamp (Velcro)
P/N 505-81010-00



5-way clamp (Silicone strap and handle)
P/N 505-81020-00

Universal 5-way clamps

The StarFish clamp allows you to hold glassware of virtually any size and comes with a choice of Silicone rubber or Velcro support straps

Each clamp features 5 telescopic arms which can be extended and locked in place to suit your needs. Using different straps on separate clamps allows you to grip the flask neck with the Silicone rubber strap for lifting, whilst the condenser above slides through the Velcro strap

Water-Distribution Manifold

Allows coolant from a single source to be evenly distributed to up to five condensers and then recombines the flow to one outlet pipe

Two manifolds are used in each set-up, one to distribute water to the condenser and one to collect coolant for recirculation or to drain. Connectors feature leak-proof shut-off valves



Water Manifold
With connector
P/N 505-81030-00



Gas/Vacuum Manifold
With connector
P/N 505-81040-00

Gas/Vacuum-Distribution Manifold

Allows gas or vacuum from a single source to be evenly distributed to up to five positions or vessels (does not control or regulate gas/vacuum flow). Connectors feature leak-proof shut-off valves

Replacement Self Adhesive Velcro Pads, 200 mm (pack of 10) 505-81070-00
Replacement Velcro Loop Strips, 200 mm (pack of 5) 505-81080-00
Replacement Silicone Straps, 200 mm (pack of 5) 505-81090-00
650 mm Support rod 505-81050-00
650 mm Support split rod 505-81060-00

➤ Magnetic Stirrer without Heating

For gentle stirring in biology and microbiology applications

Hei-Mix S

- Stir quickly and efficiently with an extended speed range up to 2,200 rpm
- Ideal for titrations due to white-colored top plate
- Space-saving unit for efficiently mixing sample sizes up to 5 liter. Small footprint of L 140 / W 126 / H 80 mm only, and the top plate comes with a diameter of 104 mm
- Long-lasting polyamide housing and PVDF top plate material



MR Hei-Mix S
P/N 503-02000-00

➤ Magnetic Stirrer Packages



MR Silver Package

This package includes:

- Magnetic Stirrer MR Hei-Tec
- Temperature sensor Pt 1000 (AISI 316Ti)
- Pt 1000 clamping system (includes support rod and attachment with cable inlet)

P/N 505-30080-00



MR Gold 1 Package

This package includes:

- Magnetic Stirrer MR Hei-Tec
- Temperature sensor Pt 1000 (AISI 316Ti)
- Pt 1000 clamping system (includes support rod and attachment with cable inlet)
- Heat-On Multi-Well system including Multi-Well holder and the following inserts: 2 x 25 ml, 2 x 50 ml, 2 x 100 ml


P/N 505-81600-00

MR Gold 2 Package

This package includes:

- Magnetic Stirrer MR Hei-Standard
- Heat-On Multi-Well system including Multi-Well holder and the following inserts: 2 x 25 ml, 2 x 50 ml, 2 x 100 ml

P/N 505-81500-00



MR Platinum Package

This package includes:

- Magnetic Stirrer MR Hei-End
- Temperature sensor Pt 1000 (AISI 316Ti)
- Base plate
- MonoBlock for 5 x 250 ml flasks
- 2 x 100-ml flask insert
- 2 x 50-ml flask insert
- 1 x 25-ml flask insert
- 5-way clamp (velcro strap)
- 5-way clamp (silicone strap & handle)
- 2 x Water Manifold
- 1 x Gas/Vacuum Manifold
- 650-mm split rod

P/N 505-81100-00

Technical Specifications - Magnetic Stirrers

| Model | MR Hei-Mix S | MR Hei-Mix L | MR Hei-Mix D | MR Hei-Standard | MR Hei-Tec | MR Hei-End |
|--|-----------------|-----------------|-----------------|--|--|--|
| P/N (230 V) | 503-02000-00 | 505-00000-00 | 505-01000-00 | 505-20000-00 | 505-30000-00 | 505-50000-00 |
| Speed range (rpm) | 0 - 2,200 | 100 - 1,400 | 100 - 1,400 | 100 - 1,400 | 100 - 1,400 | 30 - 1,400 |
| Speed accuracy (%) | ±5 | ±2 | ±2 | ±2 | ±2 | ±1 |
| Display | - | - | digital | - | digital | digital |
| Analog/digital interface | - | - | - | - | - | yes |
| Heating power (W) | - | - | - | 800 * | 800 * | 800 * |
| Hotplate temperature (°C) | - | - | - | 20 - 300 | 20 - 300 | 20 - 300 |
| Medium temperature, max. (°C) | - | - | - | 250 | 250 | 250 |
| Accuracy temperature setting (°C) | - | - | - | ±5 | ±1 | ±1 |
| External temperature sensor | - | - | - | Pt 1000 | Pt 1000 | Pt 1000 |
| Temperature accuracy with external temperature sensor (°C) | - | - | - | ±1 | ±1 | ±0.2 |
| Sensor breakage protection | - | - | - | with Pt 1000 | with Pt 1000 | with Pt 1000 |
| Temperature control | - | - | - | Micro controller | Micro controller | Micro controller |
| Temperature accuracy hotplate (°C) | - | - | - | ±5 | ±5 | ±5 |
| Safety circuit hotplate (°C) | - | - | - | 25 °C over hotplate temperature | 25 °C over hotplate temperature | 10 - 25 °C over nominal temperature |
| Stirring capacity, max. (H ₂ O) (l) | 5 | 20 | 20 | 20 | 20 | 20 |
| Load, max. (kg) | 6 | 25 | 25 | 25 | 25 | 25 |
| Power consumption (W) | 7 | 20 | 20 | 820 | 820 | 825 |
| Permissible ambient temperature (°C) | 0 - 40 | 0 - 40 | 0 - 40 | 0 - 40 | 0 - 40 | 0 - 40 |
| Max. relative humidity (%) | 80 | 80 | 80 | 80 | 80 | 80 |
| Plate diameter (mm) | Ø 104 | Ø 145 | Ø 145 | Ø 145 | Ø 145 | Ø 145 |
| Plate material | PVDF | V2A | V2A | Kera-Disk® (Silumin with ceramic coating) | Kera-Disk® (Silumin with ceramic coating) | Kera-Disk® (Silumin with ceramic coating) |
| Weight (kg) | 1.2 | 2.6 | 2.6 | 2.9 | 2.6 | 2.6 |
| Dimensions (l x w x h) (mm) | 126 x 140 x 80 | 173 x 277 x 94 | 173 x 277 x 94 | 173 x 277 x 94 | 173 x 277 x 94 | 173 x 277 x 94 |
| Protection class (DIN EN 60529) | IP 21 | IP 32 | IP 32 | IP 32 | IP 32 | IP 32 |

* 600 W for 115 V-units
Standard supply voltage: 230 V - other voltages upon request, please specify for order


Certificate

To confirm the ability for
continuous operation
of the MR series Magnetic Stirrers with hotplate

The MR series Magnetic Stirrers with hotplate feature overtemperature safety circuits according to DIN EN 61010-1:2001 and DIN EN 61010-2-010:2003 and therefore is designed for continuous operation.

This statement is made under the precondition that all units are operated in accordance with the operation manual and in accordance with good practice standards for safety in laboratories, rules for accident preventions, and compliance with directions on hazardous materials.

Schwabach, January 2015


i. V. Kurt Jelinek
Development & Production Manager


i. V. Andrea Nijßbeck
Quality Control Manager



Heidolph Instruments GmbH & Co. KG

Walpersdorfer Str. 12 • 9126 Schwabach/Germany
Phone +49 9122/9920-19 • Fax +49 9122/9920-65
Carina.Wagner@heidolph.de • www.heidolph.com

 **heidolph**
research made easy