




SBT1000S Series

SBT1000S Single Lane Swing Barrier Turnstile

SBT1011S Single Lane Swing Barrier Turnstile

(w/ controller and RFID reader)

SBT1022S Single Lane Swing Barrier Turnstile

(w/ controller and combination fingerprint & RFID reader)

Combined with mechanical, electronic, microprocessor control hardware and RFID technology. Considering availability of different dimensions, SBT1000S swing barrier is a useful solution to provide access control for people with special needs/ disabled.

The SBT1000S is a single lane swing barrier turnstile series designed for smooth and silent operation and low power demand. It's made of stainless steel which makes SBT1000S highly durable.

SBT1000S tempered-glass barriers are normally held in a locked position that deny access to the secured side. After SBT1000S's reader (RFID /fingerprint) recognized user's valid access card or fingerprint, its barriers will swing automatically, that allow the users pass to the secured side.

During emergencies, the barriers will swing automatically that ensure user can quickly access to EXIT. If power outages, the barriers will unlocked automatically that user can push the barriers to go through the lane.

Features

Reliability

- SUS304 stainless steel body provides ultra-high durability.
- High quality electrical components.
- Anti-crash function.

Safety Features

- Barriers unlocked automatically during power outages.
- Smooth and quiet operation and without exposed screws.
- Durable electrical components.


Built-in Reader Integration

- SBT1000S series already integrated with customers' preference for either card or fingerprint access control reader which greatly reduces installation time & expenses.
- SBT1000S series and associated access control readers have passed the factory test before shipment.
- ZKTeco provides the plug&play device with the lowest price in the whole industry.

Specifications

Power requirements		AC110V/220v,50/60HZ
Working temperature		-28℃~60℃
Working humidity		5%~80%
Working environment		Indoor/Outdoor (if sheltered)
Speed of throughput	RFID	Maximum 10/ minute
	Fingerprint	Maximum 10/ minute
Lane width(mm)		800
Footprint(mm*mm)		985*200
Dimensions(mm)		L=985,W=200,H=1100
Dimension with packing(mm)		L=280,W=280,H=1160
Net weight(kg)		31
Weight with packing(kg)		38
LED indicator		Y
Cabinet material		SUS304 Stainless Steel
Lid material		SUS304 Stainless Steel
Barrier material		Tempered glass (stainless speed bar optional)
Barrier movement		Swing
Emergency mode		Y
Security level		Medium
MCBF		2 million

Dimensions (mm)



SBT1000S is usually used with other types of turnstiles together. It is suitable for trolleys, wheelchair passthrough, and is not suitable for high-traffic volume.

