



T-LINK
RECORD, DISPLAY
AND ANALYSE DATA

**COMPACT CRUSHING,
SCREENING & CONVEYING
EQUIPMENT**



EVOQUIP

A TEREX BRAND

EvoQuip offers a comprehensive range of crushing, screening and conveying products to suit a wide variety of industries. The EvoQuip range starts with the Bison 35 crusher capable of outputting up to 30 tph / 34 US tph and goes up to the Cobra 290 crusher capable of outputting 290 tph / 320 US tph.





BUILDING & CONSTRUCTION

EvoQuip machines are easy to transport and can come directly to your site to crush and screen the waste from your demolition projects. Onsite recycling allows you to turn your existing waste into reusable and sellable products increasing your profits and reducing your carbon footprint.



QUARRIES

EvoQuip machines can be used in small to medium sized quarries to process natural material into sellable products. With optional add ons it is possible to produce a variety of aggregates in a single step.



PLANT HIRE

The versatility and compact nature of the EvoQuip range creates a natural addition for plant & tool hire companies. With the ease of use and weights ranging from 3.2 tonnes to 28 tonnes, the EvoQuip machines are suitable for rental into everything from light residential to heavy commercial use.



AGRICULTURE & LANDSCAPING

EvoQuip equipment can offer agricultural contractors an opportunity to diversify in the off season, helping to retain staff and ensure a steady workload throughout the year. When you are not farming use EvoQuip equipment to demolish old farm buildings, process material for lanes, driveways and drainage stones. Certain models in the range can be transported on an agricultural trailer.

Due to the very compact dimensions of EvoQuip equipment it can overcome access issues due to narrow lanes and country roads. The equipment can come directly to your home to screen top soil for home gardens or golf courses; crush material from worn driveways and brick walls.



RECYCLING

EvoQuip equipment provides the ideal solution for generating profit from waste. It is possible to process many types of waste from C&D, asphalt, concrete rubble to washout, producing and segregating sized products. This waste can then be reused as product on site or sold, resulting in reduced transport and emissions of bringing material to site; avoiding waste disposal costs and reducing virgin material used.

GRUSHERS



CRUSHING RANGE

BISON 35



HOPPER / FEEDER

Belt feeder as standard

Variable speed

JAW CRUSHER

480mm x 250mm (19" x 10") Jaw Inlet

CSS Range: 15mm to 80mm (5/8" to 3-1/4")

Hydraulic Jaw adjustment

POWERUNIT

Tier 3: 21kW / 28.5Hp Isuzu Engine

Direct drive

Stage V: Kubota V 1505

OUTPUT POTENTIAL

Up to 30tph / 34 US tph

CONVEYORS

400mm (16") Wide product conveyor

Product conveyor discharge height: 1100mm (3'4")

GENERAL

Remote control as standard

TRANSPORT

Containerisable

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	4.45m (14' 7")	1.5m (4' 11")	2.05m (6' 9")

Weight: 3,400kgs (7,496lbs)

CRUSHING RANGE

BISON 120



HOPPER / FEEDER

2.3m³ (3yd³) Hopper capacity

Grizzly feeder as standard

30mm (1-1/4") Nominal spacing grizzly

JAW CRUSHER

680mm x 400mm (27" x 16") Jaw Inlet

CSS Range: 20mm to 80mm (3/4" to 3-1/4")

Hydraulic Jaw adjustment

POWERUNIT

Stage 3A: Deutz 2.2 L3 55kW

Tier 4F & Stage V: Deutz 2.2 L3 55 kw

Hydraulic drive crusher

OUTPUT POTENTIAL

Up to 80tph / 90 US tph

CONVEYORS

800mm (32") Wide product conveyor

Product conveyor discharge height: 1.75m (5' 9")

Hydraulic folding as standard for transport

GENERAL

Jaw level sensor as standard and remote control as standard

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	5.58m (18' 4")	2.28m (7' 6")	2.74m (9')

Weight: 12,000kgs (26,455lbs)

CRUSHING RANGE

BISON 160 HYBRID



HOPPER / FEEDER

2.0m³ (2.6yd³) Hopper capacity

Integrated pre-screen as standard

JAW CRUSHER

700mm x 500mm (28"x20") Jaw inlet

CSS range: 30mm to 110mm (1.2" to 4.3")

Reverse drive function

POWERUNIT

Gen set incorporating Leroy alternator (88kVA standby)

CAT C4.4 70kW Constant Speed LRC c/w 88kVA Generator

CAT C4.4 70kW Constant Speed T3a c/w 88kVA Generator

CAT C4.4 70kW Constant Speed T4 c/w 88kVA Generator

CAT C3.6 70kW Constant Speed eu5 c/w 88kVA Generator

OUTPUT POTENTIAL

Up to 100 tph / 110 US tph

CONVEYORS

700mm (28") Wide product conveyor

Product conveyor discharge height: 2.4m (7'10")

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	6.9m (22' 8")	2.3m (7' 7")	2.6m (8' 6")

Weight: 13,500kgs (29,762lbs)

Suitable for Hooklift transporter and high cube container



BISON 280



HOPPER / FEEDER

3.6m³ (4.7yd³) Hopper capacity

Two stage grizzly feeder as standard

50mm (2") Nominal spacing grizzly

JAW CRUSHER

900mm x 600mm (36"x24") Jaw inlet

Min CSS: 40mm (1.5") Recycle / 50mm (2") in natural rock

Max CSS: 130mm (5")

Hydraulic jaw adjustment

POWERUNIT

Stage IIIA Constant Speed: John Deere 4045 126kW (169hp) (Tier 3 regions)

Tier 4 Final: Caterpillar C4.4 129kW (173Hp)

Stage V: Caterpillar C4.4 129 kW (173hp)

Direct drive to crusher via clutch and V belts

OUTPUT POTENTIAL

Up to 200 tph / 220 US tph

CONVEYORS

800mm (32") Wide product conveyor

Product conveyor discharge height: 2.9m (9'6")

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	12.4m (40' 8")	2.4m (7' 10")	3.2m (10' 6")

Weight: Tier 3: 27,700kgs (61,068lbs)

Tier 4F: 27,500kgs (60,627lbs)

*including dirt conveyor and magnet

CRUSHING RANGE

COBRA 230

HOPPER / FEEDER

2.6m³ (3.4yd³) Hopper capacity

Integrated pre-screen for fines removal

Feeder speed auto-regulates depending on crusher load

IMPACT CRUSHER

860mm (34") x 720mm (28.5") Crusher Inlet

830mm (33") Wide x 860mm (34") diameter rotor

2 High / 2 Low configuration as standard

Max OSS – 120mm (4.75") upper; 55mm (2.25") lower

Min CSS – 40mm (1.5") upper; 20mm (0.75") lower

Hydraulic adjust and hydraulic overload protection as standard

POWERUNIT

Tier 4 Final: Volvo D8 210kW (281Hp)

Stage V: Volvo D8 210kW (281Hp)

Direct drive to crusher via clutch and V Belts

OUTPUT POTENTIAL

Up to 250tph / 275 US tph

CONVEYORS

900mm (36") Wide product conveyor

Product conveyor discharge height: 3000mm (9' 10")

GENERAL

Intuitive 'Push Button' Control System

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	9.32m (30' 7")	2.43m (8')	2.99m (9' 10")

Weight (with Magnet): Tier 4F: 24,000kgs (52,911lbs)



CRUSHING RANGE

COBRA 230R

HOPPER / FEEDER

2.6m³ (3.4yd³) Hopper capacity

Integrated pre-screen for fines removal

Feeder speed auto-regulates depending on crusher load

IMPACT CRUSHER

860mm (34") x 720mm (28.5") Crusher Inlet

830mm (33") Wide x 860mm (34") diameter rotor

2 High / 2 Low configuration as standard

Hydraulic adjust and hydraulic overload protection as standard

SCREEN

2.44m x 1.2m (8' x 4') single deck mesh

Side tensioned

Screen can be lowered to horizontal to ease mesh change and maintenance

POWERUNIT

Tier 4 Final: Volvo D8 210kW (281Hp)

Stage V: Volvo D8 210kW (281Hp)

Direct drive to crusher via clutch and V Belts

OUTPUT POTENTIAL

Up to 250tph / 275 US tph

CONVEYORS

900mm (36") Wide product conveyor

500mm (20") Transfer conveyor

500mm (20") Oversize conveyor with Recirc & Stockpile

1000mm (48") Fines conveyor with 2.5m (8'2") discharge

GENERAL

Afterscreen system is quick to detach

Intuitive 'Push Button' Control System

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	13.3m (43' 7")	2.5m (8' 3")	3m (9' 10")

Weight (with Magnet): Tier 3: 29,100kgs (64,155lbs)
Tier 4F: 29,300kgs (64,595lbs)



CRUSHING RANGE

COBRA 290



HOPPER / FEEDER

3.3m³ (4.3yd³) Hopper capacity

Integrated pre-screen for fines removal

Feeder speed auto-regulates depending on crusher load

IMPACT CRUSHER

1030mm (41") x 790mm (31") Crusher Inlet

1000mm (40") Wide x 1034mm (41.5") diameter rotor

2 High / 2 Low configuration as standard

Max OSS – 150mm (6") upper; 75mm (3") lower

Min CSS – 50mm (2") upper; 20mm (0.75") lower

Hydraulic adjust and hydraulic overload protection as standard

Hinged crusher inlet lid as standard

POWERUNIT

Tier 3 Equivalent: Volvo D8 235 kW (315hp)

Tier 4 Final: Volvo D8 235kW (315Hp)

Stage V: Volvo D8 235kW (315Hp)

Direct drive to crusher via Clutch and V Belts

OUTPUT POTENTIAL

Up to 290tph / 320 US tph

CONVEYORS

1000mm (40") Wide product conveyor

Product conveyor discharge height: 3.42m (11' 3")

GENERAL

Intuitive 'Push Button' Control System

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	9.92m (32' 6")	2.55m (8' 4")	3.16m (10' 4")

Weight (with Magnet): Tier 3: 28,700kgs (63,273lbs)
Tier 4F: 28,700kgs (63,273lbs)

CRUSHING RANGE

COBRA 290R

HOPPER / FEEDER

3.3m³ (4.3yd³) Hopper capacity

Integrated pre-screen for fines removal

Feeder speed auto-regulates depending on crusher load

IMPACT CRUSHER

1030mm (41") x 790mm (31") crusher inlet

1000mm (40") x 1034mm (41.5")

Max OSS - 150mm (6") upper, 75mm (3") lower

Min CSS - 50mm (2") upper, 20mm (3/4") lower

2 high / 2 low configuration as standard

Hydraulic adjust and hydraulic overload as standard

SCREEN

2.74m x 1.5m (9'x5') single deck screen

Wide range of screen media

Side tensioned

Screen can be lowered to horizontal to ease mesh change and maintenance

POWERUNIT

Tier 3 Equivalent: Volvo D8 235 kW (315hp)

Tier 4 Final: Volvo D8 235kW (315Hp)

Stage V: Volvo D8 235kW (315Hp)

Direct drive to crusher via clutch and V belts

OUTPUT POTENTIAL

Up to 290tph / 320 US tph

CONVEYORS

1000mm (40") Wide product conveyor

500mm (20") Wide side conveyor (option)

Side conveyor (option) discharge height 2.48m (8'2")

500mm (20") Transfer conveyor

500mm (20") Oversize conveyor with Recirc & Stockpile.

1200mm (47") Fines conveyor with 3m (9'10") discharge

GENERAL

Intuitive 'Push button' control system

Afterscreen system is quick to detach

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	14.76m (48' 5")	2.9m (9' 6")	3.16m (10' 4")

Weight (with Magnet): Tier 3: 34,200kgs (75,398lbs)
Tier 4F: 34,200kgs (75,398lbs)





SCREENERS

SCREENING RANGE

COLT 600



FEEDER

3m³ (3.9yd³) Hopper capacity
1m (40") Wide
Variable speed
Maximum feed size: 300mm (12")

SCREEN

2.34m x 1.17m (8' x 4') Double deck screen
Wide range of screen media
Top Deck - Bofor Deck, Fingers, Punch Plate & Mesh
Bottom Deck - Mesh & Fingers

POWERUNIT

Tier 3: Deutz D2011 L04I - 36.4kW (48.8 Hp) @ 2300 RPM
Tier 4F / Stage IV: Deutz TD2.9L4 - 42kW (56 Hp) @ 1900 RPM
Stage 5: Deutz TD2.9L4 - 42kW (56 Hp) @ 1900 RPM

OUTPUT POTENTIAL

Up to 280 tph / 308 US tph



CONVEYORS

650mm (26") Wide fines conveyor with 2.9m (9'6") discharge
650mm (26") Wide midgrade conveyor with 2.8m (9'2") discharge
1000mm (40") Wide oversize conveyor with 2.7m (8'10") discharge
Variable speed on midgrade and oversize as standard
Ability to convert to 2 way split

TRANSPORT

Containerisable
Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	10.98m (36')	2.25m (7' 5")	2.55m (8' 4")

Weight (standard machine): 12,000kgs (26,455lbs)

SCREENING RANGE

COLT 800

FEEDER

2.9m³ (3.8yd³) Standard hopper capacity

4.7m³ (6.1yd³) Extended hopper capacity (Option)

1050mm (42") wide

Variable speed

SCREEN

2.77m x 1.22m (9' x 4') Double deck screen

Wide range of screen media

Top Deck - Bofor Deck, Fingers, Punch Plate & Mesh

Bottom Deck - Mesh & Fingers

POWERUNIT

Tier 3: Deutz TD2011 L04I - 49.4kW (66Hp) @ 2300rpm

Tier 4F / Stage IV: Cat C3.4 - 55kW (74Hp) @ 2300rpm

Stage 5: Cat C2.2 - 55Kw (74Hp) @ 2300rpm

Simple to operate



OUTPUT POTENTIAL

Up to 280 tph / 308 US tph

CONVEYORS

1050mm (42") Wide collection conveyor with SCS scraper

650mm (26") Wide fines conveyor with 3.82m (12'7") discharge

650mm (26") Wide midgrade conveyor with 3.64m (11'11") discharge

1050mm (42") Wide oversize conveyor with 3.03m (9'11") discharge

Hydraulic combined slide out and fold mechanism

Variable speed on fines, midgrade and oversize as standard

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	9.22m (30' 3")	2.5m (8' 2")	3.09m (10' 1")

Weight (standard machine): 16,700kgs (3,681lbs)



SCREENING RANGE

COLT 1000

HOPPER / FEEDER

5m³ (6.5yd³) Hopper capacity

1100mm (44") wide

Variable speed

SCREEN

4.1m (13'6") x 1.22m (4') Double deck screen

Variable screen angle

Wide range of screen media

Top Deck - Bofor Deck, Fingers, Punch Plate, 3D Punch Plate & Mesh

Bottom Deck – Mesh & Fingers

POWERUNIT

Tier 4 Final/ Stage IIIB: CAT C3.4 engine (55kW / 74hp @ 2300rpm)

Tier 3: Cat C4.4 62Kw

Stage V: Cat C2.2 55Kw

OUTPUT POTENTIAL

Up to 360 tph / 396 US tph

CONVEYORS

1000mm (40") Wide collection conveyor with SCS scraper

800mm (31") Wide fines conveyor with 3.9m (12'8") discharge

650mm (26") Wide midgrade conveyor with 3.7m (12'2") discharge

1050mm (41") Wide oversize conveyor with 3.2m (10'4") discharge

Configurable layout and ability to convert to 2 way split

Variable speed on fines, midgrade and oversize as standard

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	11.0m (35' 11")	2.50m (8' 2")	3.10m (10' 4")

Weight (standard machine): Tier 4F: 20,750kgs (45,745lbs)



SCREENING RANGE

COLT 1600



FEEDER

7m³ (9.16yd³) Hopper capacity

Heavy Duty Apron Feeder

2600mm (8' 6") wide

Variable speed

SCREEN

4.8m (16') x 1.5m (5') Double deck screen

Variable Speed

Hydraulic adjust screen angle

Single Shaft, Triple Shaft and Spaleck screenbox options

Wide range of screen media

Standard & Triple Shaft:

Top Deck: Fingerscreen, Punchplate, Bofar Deck, Woven Mesh

Bottom Deck: Fingerscreen & Woven mesh

Spaleck:

Top Deck: 3D Punchplate "Church Window, Metal & Rubber"

Bottom Deck: Flip flow Technology

POWERUNIT

Tier 3 Final / Stage IIIA Variable speed Engine - CAT 4.4 97kW (130hp)

Tier 4 Final Variable speed Engine - CAT 4.4 82kW (110hp)

Stage V: CAT C4.4 102kW (137hp) @2200rpm

98kW (131hp) @1800rpm

Hybrid option - 2 x37kW IE3 electric motors

c/w hydraulic gear pumps and electrical control panel

Easy access for maintenance

OUTPUT POTENTIAL

Up to 600 tph / 672 US tph

CONVEYORS

1200mm (48") Wide collection conveyor

900mm (35") Wide fines conveyor with 4.0m (13'1") discharge

800mm (32") Wide midgrade conveyor with 3.4m (11'2") discharge

1200mm (48") Wide oversize conveyor with 3.6m (11'10") discharge

Configurable layout and ability to convert to 2 way split

Variable speed on fines, midgrade and oversize as standard

Telescopic conveyor & Chassis Extension (300mm / 12" riser) options

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	14.95m (49' 1")	3.0m (9' 10")	3.4m (11' 2")

Weight: 31,000kgs (68,342lbs) Single shaft std configuration

34,000kgs (74,956lbs) triple shaft std configuration



SCREENING RANGE

HARRIER 220



SCREEN

2.1m (6'9") x 1.1m (3'6") Double deck screen

600mm x 1.1m (2' x 3'6") Feed in area

End tensioned as standard

POWERUNIT

Isuzu engine (21kW / 28.5hp)

Simple to operate

Stage V: Kubota V 1505

OUTPUT POTENTIAL

Up to 80tph / 90 US tph



CONVEYORS

1000mm (40") Wide collection conveyor with 1.93m (6' 4") discharge

500mm (20") Wide midgrade conveyor with 1.18m (3'10") discharge

TRANSPORT

Containerisable

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	4.36m (14' 4")	1.8m (5' 11")	2.23m (7' 4")

Weight: 3,300kgs (7,275lbs)

SCREENING RANGE

HARRIER 750

SCREEN

4.5m x 2.6m (14'8" x 8'7") Double deck grid

Split level cassettes as standard

Standard grid opening – 150mm (6"); 100mm (4") is optional

Standard bottom deck mesh – 60mm (2.4")

POWERUNIT

Tier 3: Deutz D914 53kW (71Hp) @2300rpm

Tier 4 / Stage IV: Cat C3.4 – 55kW (74Hp) @ 1800rpm)

Stage 5: Cat C2.2 – 55Kw (74Hp) @ 2300rpm

OUTPUT POTENTIAL

Up to 600tph / 660 US tph

CONVEYORS

1200mm (48") Wide product conveyor with discharge height of 3.4m (11'2")

Hydraulically folding for transport

Twin drive as standard

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	9.43m (31')	2.82m (9' 3")	3.2m (10' 6")

Weight (standard machine): 19,000kgs (41,890lbs)



SCREENING RANGE

FALCON 1220

HOPPER / FEEDER

8m³ (10.5yd³) hopper capacity

1.05m (42") wide belt feeder

Variable speed

SCREEN

Top deck: 3.66m x 1.53m (12' x 5')

Bottom deck: 3m x 1.53m (10' x 5')

Variable screen angle

POWERUNIT

Tier 3: CAT C4.4

Engine Power: 83kW (111.3Hp)

Engine Speed: 2200rpm

Stage 3A (EU Region Only): CAT C4.4

Engine Power: 98.1kW (131Hp)

Engine Speed: 1800rpm

Tier 3 Option: CAT C4.4 LRC (Optional)

Engine Power: 97kW (130Hp)

Engine Speed: 2200rpm

Tier 4 Final: CAT C4.4

Engine Power: 82kW (110Hp)

Engine Speed: 2200rpm

Stage V (EU Region Only): CAT C4.4

Engine Power: 102kW (137Hp)

Engine Speed: 2200rpm

OUTPUT POTENTIAL

Up to 275 tph / 303 US tph

CONVEYORS

11m (40") wide main conveyor

1.2m (48") wide fines conveyor with standard discharge height of 3.86m (12' 8")

650mm (26") wide mid-grade conveyor with max 4.86m (15' 11") discharge height

650mm (26") wide over-size conveyor with max 4.86m (15' 11") discharge height

TIPPING GRID

4.25m (14ft) long tipping grid as standard

Feed in width 4.77m (15' 8")

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	15.02m (49' 3")	2.55m (8' 4")	3.25m (10' 8")

Weight (with tipping grid): 24,250kgs (53, 462lbs)



SCREENING RANGE

FALCON 1230

HOPPER / FEEDER

8m³ (10.5yd³) hopper capacity
4.2m (14ft) long hopper and belt feeder
1050mm (42") wide feeder belt

SCREEN

Versatile and configurable 3 deck screen
3.66m x 1.52m (12' x 5') top & middle deck screen
3.00m x 1.52m (10' x 5') bottom deck screen
Total screening area: 15.7m² (170ft²) 3 deck
screen speed: 1120rpm max

POWERUNIT

Tier 3: CAT C4.4
Engine Power: 77kW (103Hp)
Engine Speed: 1800rpm
Stage 3A (EU Region Only): CAT C4.4
Engine Power: 98.1kW (131Hp)
Engine Speed: 1800rpm
Tier 3 Option: CAT C4.4 LRC (Optional)
Engine Power: 90kW (121Hp)
Engine Speed: 1800rpm
Stage V (EU Region Only): CAT C4.4
Engine Power: 98kW (131Hp)
Engine Speed: 1800rpm
Tier 4 Final: CAT C4.4
Engine Power: 82kW (110Hp)
Engine Speed: 1800rpm



OUTPUT POTENTIAL

Up to 300 tph / 330 US tph

CONVEYORS

1m (40") wide main conveyor
1.2m (48") wide fines conveyor with 4.4m (14' 4") discharge
650mm (26") wide mid -overs with 4.76m (15' 7") discharge
650mm (26") wide mid-fines with 4.76m (15' 7") discharge
500mm (20") wide over size conveyor with max discharge height
4.48m (14' 8")

TIPPING GRID

4.25m (14ft) long tipping grid as standard
Feed in width 4.77m (15' 8")

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	16.8m (55')	2.60m (8' 5")	3.40m (11' 3")

Weight (standard machine): 28,500kgs (62,832lbs)



CONVEYORS

CONVEYOR RANGE

TC65



CONVEYOR

Conveyor Length: 19.79m (64'11")

Belt Width: 1050mm (42")

Max Discharge Height @ 28°: 9.45m (31')

Capacity: Up to 500tph (551 US tph)

Hydraulic Folding Head Section

Belt Type: Plain - 3 Ply

Feedboot with removable 6mm wear liners

Variable speed control

Pinless Deployment

POWERUNIT

Tier 3: Deutz DT011 36kW (45hp)

Tier 4F: Deutz TD2.9 45kW (60hp)

Stage V: Deutz TC 2.9 L4 45kW (60hp)

CURRENT OPTIONS

Various options available

TRANSPORT DIMENSIONS

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	11.3m (37')	2.25m (7' 4")	2.65m (8' 8")

Weight: 13,820kgs (30,467 lbs)

Containerised shipping 40' x 9'6"

High Cube Container



CONVEYOR RANGE

TC80



CONVEYOR

Conveyor Length: 22.8m (74' 10")

Belt Width: 1050mm (42")

Max Discharge Height @ 25°: 10.41m (34' 1")

Capacity: Up to 500 tph (551 US tph)

Hydraulic Folding Head Section

Belt Type: Plain - 3 Ply

Feedboot with removable 6mm wear liners

Variable speed control

Pinless Deployment

POWERUNIT

Tier 3: Deutz DT011 36kW (45hp)

Tier 4F: Deutz TD2.9 45kW (60hp)

Stage V: Deutz TC 2.9 L4 45kW (60hp)

CURRENT OPTIONS

Various options available

TRANSPORT DIMENSIONS

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	11.88m (38' 11")	2.25m (7' 4")	2.88m (9' 5")

Weight: 16,750kgs (36,927lbs)

Containerised shipping 40' x 9'6"

High Cube Container



CONVEYOR RANGE

TC100

CONVEYOR

Conveyor Length: 22.8m (74' 10")

Belt Width: 1050mm (42")

Max Discharge Height @ 25°: 13.1m (43' 11")

Capacity: Up to 600 tph (661 US tph)

Hydraulic Folding Head Section

Belt Type: Plain - 3 Ply

Feedboot with removable 6mm wear liners

Variable speed control

Pinless Deployment



POWERUNIT

Stage 3A: CAT C4.4 83kW (111hp)

Tier 4F: CAT C4.4 82kW (110hp)

Stage V: CAT C2.2 55kW (73hp)

CURRENT OPTIONS

Various options available

TRANSPORT DIMENSIONS

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	11.9m (39')	2.8m (9' 4")	3.43m (11' 3")

Weight (Est): 21,800kgs (48,060lbs)

Containerised shipping 40' x 9'6"

High Cube Container



CONVEYOR RANGE

TC75R

CONVEYOR

Conveyor Length 22.9m (75' 1")

Belt Width 1050mm (42")

Max. Discharge Height 10.9m (34' 9") @ 23°

Production Capacity Up to 600 tph (661 US tph)

Pinless Deployment

Twin Radial Wheel drive

Automated Stockpile Program

Hydraulic Folding Head Section

POWERUNIT

Tier 3/Stage 3A: CAT C4.4 62kW (83hp)

Tier4F/Stage IV: CAT C4.4 82kW (110hp)

Stage V: Deutz TC 2.9 L4 55kW (73hp)

CURRENT OPTIONS

Various options available

TRANSPORT DIMENSIONS

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	15.2m (49' 10")	2.52m (8' 32")	3.43m (11' 3")

Weight (Est.): 19,800kgs (43,651lbs)

Containerised shipping 40' x 9'6"

High Cube Container



CONVEYOR RANGE

HLF75 HIGH LEVEL FEEDER



CONVEYOR

Conveyor Length: 22.5m (73'10")

Belt Width: 1200mm (48")

Conveyor Drive: variable speed

Max. Discharge Height: 9.8m (32' 2") @ 24°

Capacity: up to 600 tph (661 US tph)

Hydraulic fold over for transport

Hydraulic discharge height adjustment

Pinless Deployment

Rapid set up time

POWERUNIT

Stage 3A: CAT C4.4 83kW (111hp)

Tier 4/Stage VI: CAT C4.4 82kW (110hp)

Stage V: CAT C3.6

HOPPER/FEEDER

Capacity: 7m³ (9.15 cu yds)

2 Deck Vibrating grid option 3.1m x 2.45m (10' 2" x 8')

CURRENT OPTIONS

Orbital variant available

Various options available

TRANSPORT DIMENSIONS

Roll on Roll off transport (RoRo)

Containerisation, packed into 2 x 40ft high cube containers

	LENGTH	WIDTH	HEIGHT
Track Unit	19.5m (63')	2.75m (9')	3.12m (10' 2")

Weight: 23,500kgs (51,808lbs)

(+ 5,460kgs (12,037lbs) for vibrating grid)



CONVEYOR RANGE

HLF75 ORGANIC



CONVEYOR

Conveyor Length: 22.5m (73'10")

Belt Width: 1400mm (56")

Conveyor Drive: variable speed

Max. Discharge Height: 9.8m (32' 2") @ 24°

Capacity: up to 600 tph (661 US tph)

Hydraulic fold over for transport

Hydraulic discharge height adjustment

Pinless Deployment

Rapid set up time

POWERUNIT

Stage 3A: CAT C4.4 83kW (111hp)

Tier 4/Stage VI: CAT C4.4 82kW (110hp)

Stage V: CAT C3.6

HOPPER/FEEDER

Capacity: 10m³ (13 cu yds)

Variable speed 1400mm (56") Feed conveyor with Auger

Auger Max speed 195rpm

Feeder reverse function

CURRENT OPTIONS

Orbital variant available

Various options available

TRANSPORT DIMENSIONS

Roll on Roll off transport (RoRo)

Containerisation, packed into 2 x 40ft high cube containers

	LENGTH	WIDTH	HEIGHT
Track Unit	19.4 (63' 8")	2.75m (9')	3m (9' 8")

Weight: 24.350kg (53,982lbs)



CONVEYOR RANGE

LLF75 LOW LEVEL FEEDER



CONVEYOR

Conveyor Length: 22.5m (73' 10")

Belt Width: 1300mm (51")

Conveyor Drive: variable speed

Max. Discharge Height: 9.8m (32' 2")

Capacity: up to 600 tph (661 US tph)

Hydraulic fold over for transport

Hydraulic discharge height adjustment

Pinless Deployment

Rapid set up time

POWERUNIT

Stage 3A: CAT C4.4 83kW (111hp)

Tier 4/Stage VI: CAT C4.4 82kW (110hp)

Stage V: CAT C3.6

HOPPER/FEEDER

Capacity: 7m³ (9.2yds³)

Feed height: 1900mm (6' 3")

Hydraulic folding hopper flares

Target area flares down: 4.7m (15' 5") long x 2.6m (8' 6") wide

Target area flares up: 4.7m (15' 5") long x 3.49m (11' 5") wide

CURRENT OPTIONS

Orbital variant available

Various options available

TRANSPORT DIMENSIONS

Roll on Roll off transport (RoRo)

Containerisation, packed into 2 x 40ft high cube containers

	LENGTH	WIDTH	HEIGHT
Track Unit	19.74m (64' 9")	2.75m (9')	3.35m (11')

Weight: 24,700kgs (54,454lbs)



CONVEYOR RANGE

WC80 RADIAL

CONVEYOR

Conveyor Length: 22.85m (74' 10")

Belt Width: 914mm (36")

Conveyor Drive: Hydraulic or Electric

Max. Discharge Height: 9.95m (32' 7") @ 23°

Capacity: up to 300 tph (336 US tph)

Pinless Deployment

Rapid set up time

POWERUNIT

CAT 1.7T Power rating: 18.4kW (24hp)

Electric drive: 15kW

FEEDBOOT

Capacity (Low Level): 0.35m³ (0.43 yd³)

Feed in Width (Low Level): 775mm (2' 6.5")

Minimum Feed In Height (Low Level) (7°): 1534mm (5')

Capacity (Extended): 1.1m³ (1.4 Cu. Yd.)

Feed in Width (Extended): 1658mm (5' 2")

Extended Minimum Feed in Height (7°): 1793mm (5' 10")

CURRENT OPTIONS

Road Towable Available

Various options available



TRANSPORT DIMENSIONS

Roll on Roll off transport (RoRo)

2x WC80 per 40' x 9' 6" High Cube Container

	LENGTH	WIDTH	HEIGHT
Road Towable (US only)	16.17m (52' 11")	2.5m (8' 3")	3.36m (11')
Pit Portable	16.55m (54' 3")	3.1m (10' 2")	3.95m (12' 11")

Weight (with full options): 10,000kgs (22,046lbs)



ADDING VALUE TO YOUR BUSINESS



Terex Financial Services (TFS) is fully integrated into the fabric of the Terex Business

We are committed to working with our dealers and customers in developing and adding true value to their business, and assisting in the acquisition and funding of their Terex equipment.

TFS offer global solutions and through a team of dedicated people who understand the needs of our dealers and customers we can direct you to the correct financial solution for your business.

We have developed a Turnkey Funding solution to assist our dealer partners, this offer is designed to maximize a dealers potential to develop their Terex Business.

- Terex Self-funding Capability
- Improved Working Capital Management
- Demonstration Programs
- Rental Purchase Schemes
- Stock Programs

Programs are tailored by region through a panel of funders.

TFS offers a comprehensive suite of finance and leasing facilities for the end user.

The concept of adding value to your business is critical to us and this is why the TFS Team can assist you in developing the right solution for you.

These facilities can be developed and tailored to suit the individual needs of each customer.

We offer a wide range of facilities tailored by region:

- USA
- Canada
- EMEA
- JAPIC region

The range of facilities and services available are as follows;

- Leasing Solutions
- Operating lease Solutions
- Fair Market Value lease solutions
- Loans/Hire Purchase facilities
- Used Equipment Financing
- Asset Management

COMPACT WITH IMPACT



CRUSHING

BISON



COBRA



SCREENING

COLT



HARRIER



FALCON



CONVEYING

TRACKED



HIGH LEVEL



LOW LEVEL



RADIAL



The material in this document is for information only and is subject to change without notice. EvoQuip assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein.

Due to continual product development we reserve the right to change specifications without notice. Product performance figures given in this brochure are for guidance purposes only, this information does not constitute an expressed or implied warranty or guarantee, but shows test examples. These results will vary depending on application. Photographs are for illustrative purposes only; some or all of the machines in the illustrations may be fitted with optional extras. Please check with your Dealer for details on optional extras. Published and Printed in April 2021. All machines are CE Approved.

© Terex Corporation 2021

200 Coalisland Road,
Dungannon, Co. Tyrone, BT714DR

Tel: +442887718500 **Email:** EvoQuip@terex.com



terex.com/EvoQuip